

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/11/2019 Revision date: 11/5/2025 Supersedes: 10/21/2025 Version: 3.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Duro-Sheen Urethane Fortified Floor Finish
Product code : 155-20501

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Floor polishes

1.4. Supplier's details

American Cleaning Solutions
39-30 Review Avenue
Long Island City, NY, 11101
T (718) 392-8080

1.5. Emergency phone number

Emergency number : INFOTRAC: 800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. Label elements

GHS US labeling

No labeling applicable

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	CAS-No.: 7732-18-5	59.25317 – 60.56964	Not classified
Epolene E wax	CAS-No.: 68441-17-8	1 – 5	Not classified
Hoechst Wax PE 130	CAS-No.: 9002-88-4	1 – 5	Not classified
MP 320 maleated P.P.	CAS-No.: 25722-45-6	1 – 5	Not classified
Diethylene Glycol Monoethyl Ether	CAS-No.: 111-90-0	1 – 5	Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Rinse with water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

See Heading 8. Exposure controls and personal protection.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

MP 320 maleated P.P. (25722-45-6)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	3 mg/m ³ (Respirable fraction)
---------------	---

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

No special requirements.

Hand protection:

Wear chemically resistant protective gloves.

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Wear safety glasses with side shields.

Respiratory protection:

No respiratory protection needed under normal use conditions

Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: Acrylic
Odor threshold	: No data available
pH	: 8
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F
Flash point	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: Same as water
Relative density	: 1.035
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Diethylene Glycol Monoethyl Ether (111-90-0)

LD50 oral	6031 mg/kg body weight (Equivalent or similar to OECD 401, Mouse, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	9143 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (dermal)	9143 mg/kg body weight

Epolene E wax (68441-17-8)

LD50 oral rat	> 6400 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)

Hoechst Wax PE 130 (9002-88-4)

LD50 oral rat	> 15000 mg/kg (Rat, Oral)
---------------	---------------------------

Skin corrosion/irritation : Not classified
pH: 8
Serious eye damage/irritation : Not classified
pH: 8
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Diethylene Glycol Monoethyl Ether (111-90-0)

Viscosity, kinematic	3.858 mm ² /s
----------------------	--------------------------

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diethylene Glycol Monoethyl Ether (111-90-0)	
LC50 - Fish [1]	6010 mg/l (Equivalent or similar to OECD 203, 96 h, Ictalurus punctatus, Flow-through system, Fresh water, Experimental value, Lethal)
ErC50 algae	14861 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Duro-Sheen Urethane Fortified Floor Finish	
Persistence and degradability	Not established.

Water (7732-18-5)	
Persistence and degradability	Rapidly degradable

Diethylene Glycol Monoethyl Ether (111-90-0)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.2 g O ₂ /g substance
Chemical oxygen demand (COD)	1.85 g O ₂ /g substance
ThOD	1.9078849 g O ₂ /g substance
BOD (% of ThOD)	0.11 (Calculated value)

Epolene E wax (68441-17-8)	
Persistence and degradability	Not readily biodegradable in water.

MP 320 maleated P.P. (25722-45-6)	
Persistence and degradability	Biodegradability in water: no data available.

Hoechst Wax PE 130 (9002-88-4)	
Persistence and degradability	Biodegradability in soil: no data available.

12.3. Bioaccumulative potential

Duro-Sheen Urethane Fortified Floor Finish	
Bioaccumulative potential	Not established.

Diethylene Glycol Monoethyl Ether (111-90-0)	
Partition coefficient n-octanol/water (Log Pow)	-0.54 (Literature, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

Epolene E wax (68441-17-8)	
Bioaccumulative potential	Not bioaccumulative.

MP 320 maleated P.P. (25722-45-6)	
Bioaccumulative potential	No bioaccumulation data available.

Hoechst Wax PE 130 (9002-88-4)	
Bioaccumulative potential	No bioaccumulation data available.

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

Diethylene Glycol Monoethyl Ether (111-90-0)

Surface tension	52 mN/m (25 °C)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No
Other information	: Avoid release to the environment.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecological information	: Avoid release to the environment.

SECTION 14 Transport information

14.1. UN number

Not regulated for transport

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Not regulated
Proper Shipping Name (TDG)	: Not regulated
Proper Shipping Name (IMDG)	: Not regulated
Proper Shipping Name (IATA)	: Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

IMDG
Transport hazard class(es) (IMDG) : Not regulated

IATA
Transport hazard class(es) (IATA) : Not regulated

14.4. Packing group

Packing group (DOT)	: Not regulated
Packing group (TDG)	: Not regulated
Packing group (IMDG)	: Not regulated
Packing group (IATA)	: Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Water	7732-18-5	Present	Active	
Diethylene Glycol Monoethyl Ether	111-90-0	Present	Active	
Epolene E wax	68441-17-8	Present	Active	
MP 320 maleated P.P.	25722-45-6	Present	Active	
Hoechst Wax PE 130	9002-88-4	Present	Active	

15.2. International regulations

CANADA

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

No additional information available

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/5/2025
Issue date : 11/11/2019
Other information : None.

Full text of hazard classes and H-statements

H319	Causes serious eye irritation
------	-------------------------------

Duro-Sheen Urethane Fortified Floor Finish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 0 Minimal Hazard - Materials that will not burn
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.