



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name	<b>STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle</b>
CAS number	64742-47-8
Alternative number(s)	067788179885, 067788179878, 067788176815

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	General use
--------------------------	-------------

#### 1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.  
25225 Detroit Rd.  
Westlake OH 44145  
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)  
e-mail: [Autocare.regulatory@energizer.com](mailto:Autocare.regulatory@energizer.com)  
Website: <https://data.energizer.com>

Energizer Trading Ltd.  
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376  
e-mail: [ConsumerServiceEU@energizer.com](mailto:ConsumerServiceEU@energizer.com)

#### 1.4 Emergency telephone number

Emergency information service	FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM
-------------------------------	---

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.6	carcinogenicity	2	Carc. 2	H351
A.7	reproductive toxicity	2	Repr. 2	H361d
A.8	specific target organ toxicity - single exposure	2	STOT SE 2	H371
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **danger**

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs (respiratory system, blood).
H373	May cause damage to organs (blood, nervous system, eye) through prolonged or repeated exposure.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### - Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P311	If exposed or concerned: Call a poison center/doctor.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with national regulations.

### - Hazardous ingredients for labelling

naphthalene, Kerosine (petroleum), hydrodesulfurized, Heavy aromatic naphtha, toluene

## 2.3 Other hazards

Hazards not otherwise classified

Risk of explosion if heated under confinement.

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

---

Not relevant (mixture)

### Identifiers

CAS No

64742-47-8






























### 3.2 Mixtures

Description of the mixture

**STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle**

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Kerosine (petroleum), hydrodesulfurized	CAS No 64742-81-0	50 – < 75	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	10 – < 25	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	  
2-Ethylhexyl nitrate	CAS No 27247-96-7	10 – < 25	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Flam. Liq. 4 / H227	
1,2,4 trimethylbenzene	CAS No 95-63-6	5 – < 10	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
Heavy aromatic naphtha	CAS No Proprietary	1 – < 5	STOT SE 3 / H335 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
naphthalene	CAS No 91-20-3	1 – < 5	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351 STOT SE 2 / H371 STOT RE 2 / H373	 
Propylbenzene	CAS No 103-65-1  RTECS No DA8750000	1 – < 5	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
1,3,5-trimethylbenzene	CAS No 108-67-8	1 – < 5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
xylene	CAS No trade secret 1330-20-7	1 – < 5	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
cumene	CAS No 98-82-8	1 – < 5	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	  
1,2,3-Trimethylbenzene	CAS No 526-73-8	1 – < 5	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319	 



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### Remarks

For full text of abbreviations: see SECTION 16

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

- Explosive atmospheres  
Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.
- Flammability hazards  
Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.
- Ventilation requirements  
Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	C7-C8 aromatics		TLV®		200						AC-GIH® 2024
US	C9-C15 aromatics		TLV®		100						AC-GIH® 2024
US	hydrocarbon mixture (RCP method)		TLV		150		300				AC-GIH® 2016
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							AC-GIH® 2024
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	2-ethyl-1-hexanol	104-76-7	TLV®	5							AC-GIH® 2024
US	1,3,5-trimethylbenzene	108-67-8	REL	25 (10 h)	125 (10 h)						NIOSH REL
US	mesitylene	108-67-8	PEL (CA)	25	125						Cal/OSHA PEL
US	mesitylene	108-67-8	TLV®	10							AC-GIH® 2024
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							AC-GIH® 2024
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500		H	Cal/OSHA



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	sum of mandelic acid and phenylglyoxylic acid	crea	BEI®	150 mg/g	ACGIH® 2024
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2024
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2024
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2024
US	xylene	methylhippuric acids	tech_commercial, crea	BEI®	0.3 g/g	ACGIH® 2024

### Notation

crea      creatinine  
hydr      hydrolysis  
tech\_commercial      technical or commercial grades



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-Ethylhexyl nitrate	27247-96-7	DNEL	0.35 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
2-Ethylhexyl nitrate	27247-96-7	DNEL	1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-Ethylhexyl nitrate	27247-96-7	DNEL	44 µg/cm <sup>2</sup>	human, dermal	worker (industry)	chronic - local effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
1,2,4 trimethylbenzene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
xylene	trade secret 1330-20-7	DNEL	221 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	trade secret 1330-20-7	DNEL	442 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
xylene	trade secret 1330-20-7	DNEL	221 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
xylene	trade secret 1330-20-7	DNEL	442 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
xylene	trade secret 1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	250 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.08 µg/l	aquatic organisms	marine water	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.83 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.47 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	47 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	93.5 µg/kg	terrestrial organisms	soil	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	2.41 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	trade secret 1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 mg/l	aquatic organisms	freshwater	short-term (single instance)
cumene	98-82-8	PNEC	0.004 mg/l	aquatic organ-	marine water	short-term (single



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	38 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

- Lower explosion limit (LEL)	0.8 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	215 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)
--	--

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Danger of explosion, Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Harmful if inhaled.

GHS of the United Nations, annex 4: May be harmful if swallowed or in contact with skin.

#### - Acute toxicity estimate (ATE)

Inhalation: gas 4,403 ppmV/4h

Inhalation: vapor >12 mg/l/4h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Kerosine (petroleum), hydrodesulfurized	64742-81-0	dermal	>2,000 mg/kg
Solvent naphtha (petroleum), light arom.	64742-95-6	dermal	>2,000 mg/kg
2-Ethylhexyl nitrate	27247-96-7	oral	500 mg/kg
2-Ethylhexyl nitrate	27247-96-7	dermal	1,100 mg/kg
2-Ethylhexyl nitrate	27247-96-7	inhalation: vapor	11 mg/l/4h
2-Ethylhexyl nitrate	27247-96-7	inhalation: dust/mist	>5.65 mg/l/4h
1,2,4 trimethylbenzene	95-63-6	inhalation: vapor	11 mg/l/4h
Heavy aromatic naphtha	Proprietary	dermal	>2,000 mg/kg
naphthalene	91-20-3	oral	710 mg/kg
naphthalene	91-20-3	dermal	>2,500 mg/kg
naphthalene	91-20-3	inhalation: vapor	>0.4 mg/l/4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 mg/l/4h
Propylbenzene	103-65-1	inhalation: gas	32,500 ppmV/4h
1,3,5-trimethylbenzene	108-67-8	dermal	>2,000 mg/kg
1,3,5-trimethylbenzene	108-67-8	inhalation: vapor	>10.2 mg/l/4h
xylene	trade secret 1330-20-7	oral	3,523 mg/kg
xylene	trade secret 1330-20-7	dermal	1,100 mg/kg
xylene	trade secret 1330-20-7	inhalation: vapor	11 mg/l/4h
2-ethylhexan-1-ol	104-76-7	oral	2,047 mg/kg
2-ethylhexan-1-ol	104-76-7	inhalation: vapor	>0.89 mg/l/4h
ethylbenzene	100-41-4	oral	3,500 mg/kg
ethylbenzene	100-41-4	inhalation: vapor	11 mg/l/4h
toluene	108-88-3	inhalation: gas	7.6 ppmV/4h
toluene	108-88-3	inhalation: vapor	28.1 mg/l/4h

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitization

Based on available data, the classification criteria are not met.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Suspected of causing cancer.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Propylbenzene	98-82-8	2B	
ethylbenzene	100-41-4	2B	
cumene	98-82-8	2B	
xylene	1330-20-7	3	
naphthalene	91-20-3	2B	
toluene	108-88-3	3	

#### Legend

- 2B Possibly carcinogenic to humans  
3 Not classifiable as to carcinogenicity in humans

#### National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
cumene	98-82-8	Reasonably anticipated to be a human carcinogen	13th Report on Carcinogens
naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens

### Reproductive toxicity

Suspected of damaging the unborn child.

### Specific target organ toxicity - single exposure

May cause damage to organs (respiratory system, blood). May cause drowsiness or dizziness.

Hazard category	Target organ	Exposure route
2	respiratory system	if exposed
2	blood	if exposed

### Specific target organ toxicity - repeated exposure

May cause damage to organs (blood, nervous system, eye) through prolonged or repeated exposure.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Hazard category	Target organ	Exposure route
2	blood	if exposed
2	nervous system	if exposed
2	eye	if exposed

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LL50	2 – 5 mg/l	fish	96 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	1.4 mg/l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1 mg/l	algae	72 h
Solvent naphtha (petroleum), light arom.	64742-95-6	LL50	8.2 mg/l	fish	96 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	4.5 mg/l	aquatic invertebrates	48 h
2-Ethylhexyl nitrate	27247-96-7	LC50	2 mg/l	fish	96 h
2-Ethylhexyl nitrate	27247-96-7	EC50	0.83 mg/l	aquatic invertebrates	48 h
2-Ethylhexyl nitrate	27247-96-7	ErC50	>2.53 mg/l	algae	72 h
2-Ethylhexyl nitrate	27247-96-7	NOEC	1.52 mg/l	fish	96 h
2-Ethylhexyl nitrate	27247-96-7	LOEC	2.53 mg/l	algae	72 h
1,2,4 trimethybenzene	95-63-6	LC50	7.72 mg/l	fish	96 h
1,2,4 trimethybenzene	95-63-6	EC50	2.356 mg/l	algae	96 h
Heavy aromatic naphtha	Proprietary	LC50	2 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
Heavy aromatic naphtha	Proprietary	LC50	3 mg/l	fathead minnow	72 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	water flea (Daphnia)	48 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	algae	96 h
Heavy aromatic naphtha	Proprietary	LL50	5 mg/l	fish	96 h
Heavy aromatic naphtha	Proprietary	EL50	1.4 mg/l	aquatic invertebrates	48 h
Heavy aromatic naphtha	Proprietary	LOEL	1 mg/l	algae	72 h
naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h
Propylbenzene	103-65-1	LC50	1.55 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
Propylbenzene	103-65-1	EC50	2 mg/l	water flea (Daphnia)	24 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	0.89 mg/l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	10 mg/l	fish	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EC50	15.41 mg/l	microorganisms	40 h
2-Ethylhexyl nitrate	27247-96-7	EC50	>1,000 mg/l	microorganisms	3 h
Heavy aromatic naphtha	Proprietary	EL50	0.89 mg/l	aquatic invertebrates	21 d
Heavy aromatic naphtha	Proprietary	LOEL	1.2 mg/l	aquatic invertebrates	21 d
naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
naphthalene	91-20-3	NOEC	0.37 mg/l	fish	40 d
naphthalene	91-20-3	LOEC	0.38 mg/l	fish	40 d
1,3,5-trimethylbenzene	108-67-8	NOEC	0.4 mg/l	aquatic invertebrates	21 d
xylene	trade secret 1330-20-7	EL50	2.9 mg/l	aquatic invertebrates	21 d
xylene	trade secret 1330-20-7	ErC50	4.36 mg/l	algae	73 h
xylene	trade secret 1330-20-7	EC50	2.2 mg/l	algae	73 h
xylene	trade secret 1330-20-7	NOEC	>1.3 mg/l	fish	56 d
xylene	trade secret 1330-20-7	LOEC	3.16 mg/l	aquatic invertebrates	21 d
cumene	98-82-8	EC50	1.5 mg/l	aquatic invertebrates	21 d
cumene	98-82-8	LC50	>3 mg/l	aquatic invertebrates	21 d
cumene	98-82-8	NOEC	0.38 mg/l	fish	28 d
ethylbenzene	100-41-4	LC50	3.6 mg/l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEL	1.7 mg/l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	NOEC	0.96 mg/l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEC	1.7 mg/l	aquatic invertebrates	7 d
toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number

IMDG-Code UN 1268

ICAO-TI UN 1268

### 14.2 UN proper shipping name

IMDG-Code PETROLEUM DISTILLATES, N.O.S.

ICAO-TI Petroleum distillates, n.o.s.

### 14.3 Transport hazard class(es)

IMDG-Code 3

ICAO-TI 3

### 14.4 Packing group

**STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle**

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	Kerosine (petroleum), hydrodesulfurized
<b>14.6 Special precautions for user</b>	
There is no additional information.	
<b>14.7 Transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	

**Information for each of the UN Model Regulations**

**Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Not subject to transport regulations.

Reportable quantity (RQ) 4,414 lbs (2,004 kg) (naphthalene) (xylene)

**International Maritime Dangerous Goods Code (IMDG) - Additional information**

Particulars in the shipper's declaration UN1268, PETROLEUM DISTILLATES, N.O.S., (contains: Kerosine (petroleum), hydrodesulfurized, 1,2,4 trimethybenzene), 3, III, 38°C c.c., MARINE POLLUTANT

Marine pollutant yes (hazardous to the aquatic environment)

Danger label(s) 3, fish and tree



Special provisions (SP) 223, 955

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-E

Stowage category A

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Particulars in the shipper's declaration UN1268, Petroleum distillates, n.o.s., (contains: Kerosine (petroleum), hydrodesulfurized, 1,2,4 trimethybenzene), 3, III

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09



Special provisions (SP) A3  
Excepted quantities (EQ) E1  
Limited quantities (LQ) 10 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

##### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

##### Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
Propylbenzene	98-82-8		1987-01-01
ethylbenzene	100-41-4		1987-01-01
cumene	98-82-8		1987-01-01
1,2,4 trimethybenzene	95-63-6		1987-01-01
xylene	1330-20-7		1987-01-01
naphthalene	91-20-3		1987-01-01
toluene	108-88-3		1987-01-01

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethylbenzene	100-41-4		1 2 3	1000 (454)
cumene	98-82-8		3 4	5000 (2270)
xylene	1330-20-7		1 3 4	100 (45,4)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)

### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

### Clean Air Act

none of the ingredients are listed

### Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

Name of substance	CAS No	Listed in	Special conditions	Excluded transactions	DEA - code	Concentration limit
toluene	108-88-3	List II chemicals	SC-6594	excl-trans-12	6594	35% by Weight or Volume

### Legend

- excl-trans-12 Excluded transactions: Domestic and import transactions in chemical mixtures that contain acetone, ethyl ether, 2-butanone, and/or toluene, unless regulated because of being formulated with other List I or List II chemical(s) above the concentration limit.
- List II chemicals The term "list II chemical" means a chemical (other than a list I chemical) specified by regulation of the Attorney General as a chemical that is used in manufacturing a controlled substance in violation of this subchapter.
- SC-6594 Exports only; Limit applies to toluene or any combination of acetone, ethyl ether, 2-butanone, methyl isobutyl ketone, and toluene if present in the mixture by summing the concentrations for each chemical.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### STP Ultra 5 in 1 Diesel Fuel System Cleaner-bottle

Version number: 8.0  
Replaces version of: 2023-08-23 (7)

Revision: 2025-05-09

---

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.