



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 1: Identification

1.1 Product identifier

Trade name **STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle**
Alternative number(s) 071153186095

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
e-mail: Autocare.regulatory@energizer.com
Website: <http://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.6	carcinogenicity	1B	Carc. 1B	H350
A.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS06, GHS07,
GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

- Precautionary statements

P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P311	Call a poison center/doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Distillates (petroleum), hydrodesulfurized middle,
Distillates (petroleum), hydrotreated light, naphthalene, Polyether amine

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.


SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Distillates (petroleum), hydrotreated light	CAS No 64742-47-8	10 - < 25	Acute Tox. 3 / H331 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Polyether amine	CAS No Proprietary	10 - < 25	STOT SE 3 / H335	
Distillates (petroleum), hydro-treated middle	CAS No 64742-46-7	10 - < 25	Acute Tox. 4 / H332 STOT SE 3 / H335 Flam. Liq. 3 / H226	
Straight-run Kerosene	CAS No 64741-44-2	5 - < 10	Acute Tox. 4 / H332 Flam. Liq. 3 / H226	
Distillates (petroleum), hydrodesulfurized middle	CAS No 64742-80-9	5 - < 10	Acute Tox. 4 / H332 Carc. 1B / H350 Flam. Liq. 3 / H226	
Distillates (petroleum), hydrodesulfurized light catalytic cracked	CAS No 68333-25-5	5 - < 10	Acute Tox. 4 / H332 Carc. 1B / H350 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Jet A-1	CAS No 8008-20-6	5 - < 10	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Kerosine (petroleum), hydrodesulfurized	CAS No 64742-81-0	1 - < 5	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Heavy aromatic naphtha	CAS No Proprietary	1 - < 5	STOT SE 3 / H335 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Substituted aliphatic amine	CAS No Proprietary	1 - < 5	STOT SE 3 / H335	
Distillates (petroleum), light hydrocracked	CAS No 64741-77-1	1 - < 5	Acute Tox. 3 / H331 Carc. 2 / H351 Flam. Liq. 3 / H226	
naphthalene	CAS No 91-20-3	< 1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351 STOT SE 2 / H371 STOT RE 2 / H373	

For full text of abbreviations: see SECTION 16.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	Kerosine - unspecified	64742-81-0	TLV®		200					vap, Hy-Carb, H	AC-GIH® 2023
US	Kerosine (petroleum)	8008-20-6	REL		100 (10 h)						NIOSH REL
US	Kerosine (petroleum) (jet fuels, JP 5)	8008-20-6	TLV®		200					vap, Hy-Carb, H	AC-GIH® 2023
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5						Cal/OSHA PEL



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1000
US	naphthalene	91-20-3	TLV®	10						H	ACGIH® 2023

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

H

absorbed through the skin

HyCarb

calculated as hydrocarbons

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

vap

as vapors

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Straight-run Kerosene	64741-44-2	DNEL	16.4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Straight-run Kerosene	64741-44-2	DNEL	1,501 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Straight-run Kerosene	64741-44-2	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	DNEL	27.3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	DNEL	2,230 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	DNEL	2.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	68.34 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	4,288 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥141 °C at 101.3 kPa
Flash point	38 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Toxic if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Inhalation: vapor 8.597 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
Distillates (petroleum), hydrotreated middle	64742-46-7	inhalation: vapor	11 mg/l/4h
Distillates (petroleum), hydrotreated middle	64742-46-7	inhalation: dust/mist	4.6 mg/l/4h
Straight-run Kerosene	64741-44-2	inhalation: vapor	11 mg/l/4h
Straight-run Kerosene	64741-44-2	inhalation: dust/mist	>2.53 mg/l/4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: vapor	11 mg/l/4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: dust/mist	4.6 mg/l/4h
Jet A-1	8008-20-6	inhalation: vapor	>5.28 mg/l/4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: vapor	11 mg/l/4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: dust/mist	4.65 mg/l/4h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	inhalation: vapor	>5.28 mg/l/4h
Distillates (petroleum), light hydrocracked	64741-77-1	inhalation: vapor	3.6 mg/l/4h
naphthalene	91-20-3	oral	710 mg/kg
naphthalene	91-20-3	inhalation: vapor	>0.4 mg/l/4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 mg/l/4h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
naphthalene	91-20-3	2B	

Legend

2B Possibly carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	nervous system	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	rainbow trout (<i>Oncorhynchus mykiss</i>)	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	goldfish (<i>Carassius auratus</i>)	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	water flea (<i>Daphnia</i>)	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	algae	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1 mg/l	algae	72 h
Distillates (petroleum), hydrotreated middle	64742-46-7	LL50	>100 mg/l	fish	24 h
Distillates (petroleum), hydrotreated middle	64742-46-7	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Straight-run Kerosene	64741-44-2	LL50	>100 mg/l	fish	24 h
Straight-run Kerosene	64741-44-2	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	LL50	>100 mg/l	fish	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Jet A-1	8008-20-6	LL50	5 mg/l	fish	96 h
Jet A-1	8008-20-6	EL50	1.4 mg/l	aquatic invertebrates	48 h
Jet A-1	8008-20-6	LOEL	1 mg/l	algae	72 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LL50	>0.3 mg/l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LC50	>0.21 mg/l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.32 mg/l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LL50	5 mg/l	fish	96 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	1.4 mg/l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1 mg/l	algae	72 h
Heavy aromatic naphtha	Proprietary	LC50	2 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
Heavy aromatic naphtha	Proprietary	LC50	3 mg/l	fathead minnow	72 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	water flea (Daphnia)	48 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	algae	96 h
Heavy aromatic naphtha	Proprietary	LL50	5 mg/l	fish	96 h
Heavy aromatic naphtha	Proprietary	EL50	1.4 mg/l	aquatic invertebrates	48 h
Heavy aromatic naphtha	Proprietary	LOEL	1 mg/l	algae	72 h
Distillates (petroleum), light hydrocracked	64741-77-1	LL50	>100 mg/l	fish	24 h
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	180 mg/l	aquatic invertebrates	24 h
naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrotreated middle	64742-46-7	EL50	>1,000 mg/l	microorganisms	40 h
Straight-run Kerosene	64741-44-2	EL50	>1,000 mg/l	microorganisms	40 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 mg/l	microorganisms	40 h
Jet A-1	8008-20-6	EL50	0.89 mg/l	aquatic invertebrates	21 d
Jet A-1	8008-20-6	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.22 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EC50	0.17 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	NOEC	0.038 mg/l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	0.89 mg/l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Heavy aromatic naphtha	Proprietary	EL50	0.89 mg/l	aquatic invertebrates	21 d
Heavy aromatic naphtha	Proprietary	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	>1,000 mg/l	microorganisms	40 h
naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
naphthalene	91-20-3	NOEC	0.37 mg/l	fish	40 d
naphthalene	91-20-3	LOEC	0.38 mg/l	fish	40 d



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1268
IMDG-Code	UN 1268
ICAO-TI	UN 1268

14.2 UN proper shipping name

DOT	Petroleum distillates, n.o.s.
-----	-------------------------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle



Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

IMDG-Code	PETROLEUM DISTILLATES, N.O.S.
ICAO-TI	Petroleum distillates, n.o.s.
14.3 Transport hazard class(es)	
DOT	3
IMDG-Code	3
ICAO-TI	3
14.4 Packing group	
DOT	III
IMDG-Code	III
ICAO-TI	III
14.5 Environmental hazards	hazardous to the aquatic environment
14.5.1 Additional information	LTD QTY
Environmentally hazardous substance (aquatic environment)	Jet A-1
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1268, Petroleum distillates, n.o.s., (contains: Distillates (petroleum), hydrotreated middle, Straight-run Kerosene), 3, III, environmentally hazardous
Reportable quantity (RQ)	12,276 lbs (5,573 kg) (benzene) (naphthalene)
Danger label(s)	3, fish and tree
 	
Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	144, 363, B1, IB3, T4, TP1, TP29, LTD QTY
ERG No	128



Safety Data Sheet



acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle


Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN1268, PETROLEUM DISTILLATES, N.O.S., (contains: Distillates (petroleum), hydrotreated middle, Straight-run Kerosene), 3, III, 38°C c.c., MARINE POLLUTANT
Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	3, fish and tree
 	
Special provisions (SP)	223, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-E
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN1268, Petroleum distillates, n.o.s., (contains: Distillates (petroleum), hydrotreated middle, Straight-run Kerosene), 3, III
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from listing



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
naphthalene	91-20-3		1987-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
naphthalene	91-20-3		1 2 3 4	100 (45,4)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
ethylbenzene	100-41-4		cancer
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Country	Inventory	Status
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed (ACTIVE)	Toxic Substance Control Act (TSCA): all ingredients are listed (ACTIVE) or exempt from listing	yes
15.1		National inventories: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Abbr.	Descriptions of used abbreviations
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Ethanol Fuel System Cleaner + Fuel Stabilizer - bottle

Version number: 7.2
Replaces version of: 2023-07-06 (6)

Revision: 2023-09-11

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H371	May cause damage to organs.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.