



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

SECTION 1: Identification

1.1 Product identifier

Trade name **STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol**
Alternative number(s) 071153182745

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
e-mail: Autocare.regulatory@energizer.com
Website: <http://data.energizer.com>

1.4 Emergency telephone number

Emergency information service
FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.6	carcinogenicity	1	Carc. 1	H350
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
B.3	flammable aerosol	1	Flam. Aerosol 1	H222
B.5	gases under pressure	C	Press. Gas C	H280

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS04, GHS06,
GHS07, GHS08



- Hazard statements

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P311	Call a poison center/doctor.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

- Hazardous ingredients for labelling

Hydrotreated heavy petroleum distillates, Distillates (petroleum), hydrotreated light, Calcium Sulfonate, Hydrotreated Heavy Alkanes

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Distillates (petroleum), hydrotreated light	CAS No 64742-47-8	25 - < 50	Acute Tox. 3 / H331 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Hydrotreated heavy petroleum distillates	CAS No trade secret	25 - < 50	Acute Tox. 4 / H332 Carc. 1 / H350	
isobutane	CAS No 75-28-5	5 - < 10	Flam. Gas 1 / H220 Press. Gas C / H280	
Calcium Sulfonate	CAS No Proprietary	5 - < 10	Skin Sens. 1B / H317	
propane	CAS No 74-98-6	1 - < 5	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	
Hydrotreated Heavy Alkanes	CAS No trade secret	1 - < 5	Acute Tox. 4 / H332	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

For full text of abbreviations: see SECTION 16.

Legend: Press. Gas

Press. Gas C: Gas under pressure: compressed gas

Press. Gas L: Gas under pressure: liquefied gas

Press. Gas R: Gas under pressure: refrigerated liquefied gas

Press. Gas D: Gas under pressure: dissolved gas.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	propane	74-98-6	PEL (CA)	1,000	1,800						Cal/OSHA PEL
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1000
US	propane	74-98-6	TLV®							oxygen, Simple Asp., E	ACGIH® 2023
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				E	ACGIH® 2023

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur
 E explosive
 oxygen Adequate oxygen delivery to the tissues is necessary for sustaining life
 Simple Asp. simple asphyxiants



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Notation

STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	not determined
Particle	not relevant (aerosol)
Odor	characteristic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	-88.6 °C at 1,013 hPa
Evaporation rate	Not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Explosive limits

- Lower explosion limit (LEL)	5 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

9.2 Other information

Propellant content	9.982 %
Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Toxic if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

- Acute toxicity estimate (ATE)
Inhalation: vapor 7.442 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
Hydrotreated heavy petroleum distillates	trade secret	inhalation: vapor	11 mg/l/4h
Hydrotreated heavy petroleum distillates	trade secret	inhalation: dust/mist	2.18 mg/l/4h
Hydrotreated Heavy Alkanes	trade secret	inhalation: vapor	11 mg/l/4h
Hydrotreated Heavy Alkanes	trade secret	inhalation: dust/mist	2.18 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	nervous system	if exposed

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	rainbow trout (<i>Oncorhynchus mykiss</i>)	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	LC50	>1,000 mg/l	goldfish (<i>Carassius auratus</i>)	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	water flea (<i>Daphnia</i>)	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	EC50	>1,000 mg/l	algae	72 h
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1 mg/l	algae	72 h
Hydrotreated heavy petroleum distillates	trade secret	LC50	>5,000 mg/l	rainbow trout (<i>Oncorhynchus mykiss</i>)	96 h
Hydrotreated heavy petroleum distillates	trade secret	LC50	>1,000 mg/l	water flea (<i>Daphnia</i>)	48 h
Hydrotreated heavy petroleum distillates	trade secret	LL50	>100 mg/l	fish	96 h
Hydrotreated heavy petroleum distillates	trade secret	EL50	>10,000 mg/l	aquatic invertebrates	24 h
isobutane	75-28-5	LC50	49.9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19.37 mg/l	algae	96 h
propane	74-98-6	LC50	49.9 mg/l	fish	96 h
propane	74-98-6	EC50	19.37 mg/l	algae	96 h
Hydrotreated Heavy Alkanes	trade secret	LL50	>100 mg/l	fish	96 h
Hydrotreated Heavy Alkanes	trade secret	EL50	>10,000 mg/l	aquatic invertebrates	24 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrotreated light	64742-47-8	LOEL	1.2 mg/l	aquatic invertebrates	21 d
Hydrotreated heavy petroleum distillates	trade secret	NOELR	≥1,000 mg/l	fish	14 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

SECTION 14: Transport information

14.1 UN number

DOT	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

DOT	Aerosols
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

DOT	2.1
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, 2.1
Danger label(s)	2.1



Special provisions (SP)	N82
ERG No	126



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN1950, AEROSOLS, 2.1, -88.6°C c.c.
Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, flammable, 2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE) or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
isobutane	75-28-5	Flammable substance	f	10000
propane	74-98-6	Flammable substance	f	10000

Legend

f Flammable gas.

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Distillates (petroleum), hydrotreated light	64742-47-8	solvents	
Hydrotreated heavy petroleum distillates	64742-54-7		EC Annex VI CMRs - Cat. 1B
isobutane	75-28-5	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
propane	68476-86-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Hydrotreated Heavy Alkanes	64742-52-5	solvents	EC Annex VI CMRs - Cat. 1B

- Toxic or Hazardous Substance List (MA-TURA)

none of the ingredients are listed

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
isobutane		N	
propane	74-98-6	A, O	
propane		N	
propane		A	gases

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
 gases Refers to displacement of air asphyxiation hazard.
 N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
 O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
isobutane	75-28-5		F4
propane	74-98-6		F4

Legend

F4 Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANE, 2-METHYL-	75-28-5	
PROPANE	74-98-6	

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
isobutane	106-97-8	T, F
propane	74-98-6	T
propane	74-98-6	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Country	Inventory	Status
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		- Precautionary statements: change in the listing (table)	yes
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.	yes
3.2		Legend: Press. Gas: Press. Gas C: Gas under pressure: compressed gas Press. Gas L: Gas under pressure: liquefied gas Press. Gas R: Gas under pressure: refrigerated liquefied gas Press. Gas D: Gas under pressure: dissolved gas.	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.	yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed	Toxic Substance Control Act (TSCA): all ingredients are listed (ACTIVE) or exempt from listing	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Abbr.	Descriptions of used abbreviations
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant + Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Abbr.	Descriptions of used abbreviations
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEL	Lowest Observed Effect Level
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOELR	No Observed Effect Loading Rate
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
Press. Gas	Gas under pressure
Press. Gas C	Compressed gas
Press. Gas D	Dissolved gas
Press. Gas L	Liquefied gas
Press. Gas R	Refrigerated liquefied gas
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP 3-in-1 Penetrant & Lubricant+Rust Protection Aerosol

Version number: 8.2
Replaces version of: 2022-08-16 (7)

Revision: 2023-09-11

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.
OSHA002	May displace oxygen and cause rapid suffocation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.