

Safety Data Sheet



Revision Number: 005.0

Issue date: 03/28/2025

1. IDENTIFICATION

Product name: OSI® H2U® High Performance Acrylic Urethane Sealant Window, Door & Siding Clear
IDH number: 1256965

Product type/Recommended use: Sealant

Restriction of Use: None identified

Company address: Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

Region: United States

Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

This product contains one or more components that are exempt from listing on the U. S. Toxic Substances Control Act (TSCA) inventory because a polymer exemption has been granted in accordance with 40 CFR 723.250.
This product contains one or more components regulated under a Significant New Use Rule (SNUR) by the US EPA. See Section 15 for more information.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.
H361 - SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapors, mist, or spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Response: P280 - Wear protective gloves, clothing, eye and face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P308+P313 - IF exposed or concerned: Get medical attention.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

IDH number: 1256965

Product name: OSI® H2U® High Performance Acrylic Urethane Sealant Window, Door & Siding Clear
Page 1 of 6

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Ethylene glycol	107-21-1	1 - 5
Reaction mass of pentamethyl-4-piperidylsebacates	1065336-91-5	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air in case of accidental inhalation of vapours.
Skin contact:	Wash affected area immediately with soap and water.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Consult a physician if necessary.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Carbon dioxide, foam, powder Water fog.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Use water spray to keep fire exposed containers cool and disperse vapors.
Unusual fire or explosion hazards:	None expected.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Absorb spill with inert material. Shovel material into appropriate container for disposal.

7. HANDLING AND STORAGE

Handling:	Avoid prolonged or repeated skin contact with this material. Keep out of the reach of children.
Storage:	For safe storage, store at or above 0 °C (32°F) Keep from freezing. Store in a cool, dry area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil (petroleum), highly refined	5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ TWA mist 5 mg/m ³ PEL Mist.	None	None
Ethylene glycol	25 ppm TWA Vapor fraction 50 ppm STEL Vapor fraction 10 mg/m ³ STEL Aerosol, inhalable.	None	None	None
Silica, amorphous, fumed, cryst.-free	3 mg/m ³ TWA Respirable particles. 10 mg/m ³ TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m ³ TWA 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None

Engineering controls:	Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
Respiratory protection:	No personal respiratory protective equipment normally required.
Eye/face protection:	None required in normal use.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Off white
Odor:	Mild, Acrylic
Odor threshold:	Not available.
pH:	7.3 - 8.5
Vapor pressure:	15 mm hg (20.0 °C (68°F))
Boiling point/range:	100 °C (212°F)
Melting point/ range:	Not available.
Density/Relative density:	1.0425 - 1.0665
Relative vapor density:	Not available.
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	< 0.5 (Butyl acetate = 1)
Solubility:	Soluble
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	0.4 %; 63 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Dynamic viscosity:	200,000 - 300,000 cp
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen.
Incompatible materials:	None
Reactivity:	Not available.
Conditions to avoid:	Do not freeze.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation.
Skin contact:	May cause allergic skin reaction.
Eye contact:	May cause irritation.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Ethylene glycol	Oral LD50 (Rat) = 5.89 g/kg Oral LD50 (Mouse) = 14.6 g/kg Dermal LD50 (Rabbit) = 9,530 mg/kg
Reaction mass of pentamethyl-4-piperidylsebacates	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Ethylene glycol	Irritant		Blood Bone Marrow Central nervous system Developmental Eyes Kidney Liver Metabolic
Reaction mass of pentamethyl-4-piperidylsebacates			

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethylene glycol	No	No	No
Reaction mass of pentamethyl-4-piperidylsebacates	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. This product contains one or more components with a Polymer Exemption in accordance with 40 CFR 723.250.
TSCA 5(a) SNUR:	This product contains the following component(s) subject to a Significant New Use Rule (SNUR) by the US EPA: Mercury (CAS # 7439-97-6). The SNUR is codified at Section number: 40 CFR 721.10068 None above reporting de minimis
TSCA 12 (b) Export Notification:	None above reporting de minimis.
CERCLA/SARA Section 302 EHS:	Please refer to the GHS classification in Section 2
CERCLA/SARA Section 311/312:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).
CERCLA/SARA Section 313:	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 9, 11, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/28/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.