



Revision Number: 005.0

Issue date: 03/31/2025

**1. IDENTIFICATION**

**Product name:** OSI® H2U® High Performance Acrylic Urethane Sealant Window, Door & Siding White 001 **IDH number:** 1256934

**Product type/Recommended use:** Sealant

**Restriction of Use:** None identified **Region:** United States

**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067


**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

This product contains one or more components that are exempt from listing on the U. S. Toxic Substances Control Act (TSCA) inventory because a polymer exemption has been granted in accordance with 40 CFR 723.250.

**2. HAZARDS IDENTIFICATION**

| EMERGENCY OVERVIEW |  |
|--------------------|--|
| <b>WARNING:</b>    | H319 - CAUSES SERIOUS EYE IRRITATION.<br>H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. |

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| EYE IRRITATION                                     | 2A              |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |



**Precautionary Statements**

**Prevention:** P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash affected area thoroughly after handling.  
P280 - Wear eye and face protection.

**Response:** P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 - Get medical attention if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical attention.

**Storage:** Not prescribed

**Disposal:** P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                | CAS Number | Weight %* |
|---|------------|-----------|
| Limestone   | 1317-65-3  | 10 - 30   |
| Titanium dioxide < 1% particles with diameter ≤ 10 µm | 13463-67-7 | 1 - 5     |
| Ethylene glycol                                       | 107-21-1   | 1 - 5     |
| Quartz (SiO <sub>2</sub> ), <1% respirable            | 14808-60-7 | 0.1 - 1   |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

|  |  |
|--|--|
| <b>Inhalation:</b>   | Move to fresh air in case of accidental inhalation of vapours.   |
| <b>Skin contact:</b>   | Wash affected area immediately with soap and water.  |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.   |
| <b>Ingestion:</b>  | Consult a physician if necessary. Do not induce vomiting.  |
| <b>Most important symptoms and effects (acute and delayed):</b>                  | The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information. |
| <b>Indication of any immediate medical attention / special treatment needed:</b> | Not available.   |

### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Carbon dioxide, foam, powder Water fog.  |
| <b>Improper extinguishing agents:</b>     | Not available.   |
| <b>Special firefighting procedures:</b>   | Use water spray to keep fire exposed containers cool and disperse vapors.  |
| <b>Unusual fire or explosion hazards:</b> | May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.                             |
| <b>Hazardous combustion products:</b>     | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen. |

### 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.   |
| <b>Clean-up methods:</b>          | Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations. |

## 7. HANDLING AND STORAGE

**Handling:** Avoid prolonged or repeated skin contact with this material. Keep out of the reach of children.

**Storage:** For safe storage, store at or above 0 °C (32°F)  
Keep from freezing. Store in a cool, dry area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                                | ACGIH TLV   | OSHA PEL  | AIHA WEEL | OTHER |
|---|---|---|-----------|-------|
| Limestone   | 10 mg/m3 TWA<br>Inhalable particles.<br>3 mg/m3 TWA<br>Respirable particles.<br>10 mg/m3 TWA<br>Total dust. | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>15 mg/m3 TWA<br>Total dust.<br>15 MPPCF TWA<br>Respirable fraction. | None      | None  |
| Titanium dioxide < 1% particles with diameter ≤ 10 μm | 0.2 mg/m3 TWA<br>Respirable nanoscale particles<br>2.5 mg/m3 TWA<br>Respirable finescale particles          | 15 mg/m3 PEL<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>15 mg/m3 TWA<br>Total dust.<br>15 MPPCF TWA<br>Respirable fraction.  | None      | None  |
| Ethylene glycol                                       | 25 ppm TWA<br>Vapor fraction<br>50 ppm STEL<br>Vapor fraction<br>10 mg/m3 STEL<br>Aerosol, inhalable.       | None  | None      | None  |
| White mineral oil (petroleum), highly refined         | 5 mg/m3 TWA<br>Inhalable fraction.  | 5 mg/m3 TWA mist<br>5 mg/m3 PEL Mist.   | None      | None  |
| Silica, amorphous, fumed, cryst.-free                 | 3 mg/m3 TWA<br>Respirable particles.<br>10 mg/m3 TWA<br>Inhalable particles.                                | 20 MPPCF TWA<br>0.8 mg/m3 TWA<br>50 MPPCF TWA<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>15 mg/m3 TWA<br>Total dust.<br>15 MPPCF TWA<br>Respirable fraction.                                      | None      | None  |
| Quartz (SiO <sub>2</sub> ), <1% respirable            | 0.025 mg/m3 TWA<br>Respirable fraction.   | 0.05 mg/m3 TWA<br>(Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m3<br>OSHA ACT<br>(Respirable dust.)<br>0.05 mg/m3 PEL<br>Respirable dust.<br>2.4 MPPCF TWA<br>Respirable<br>0.1 mg/m3 TWA<br>Respirable | None      | None  |

|                                |   |
|--------------------------------|---|
| <b>Engineering controls:</b>   | Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.                               |
| <b>Respiratory protection:</b> | If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided. |
| <b>Eye/face protection:</b>    | Safety goggles or safety glasses with side shields.   |
| <b>Skin protection:</b>        | Use impermeable gloves and protective clothing as necessary to prevent skin contact.  |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>Physical state:</b>  | Liquid   |
| <b>Color:</b>   | White  |
| <b>Odor:</b>  | mild, Acrylic  |
| <b>Odor threshold:</b>  | Not available.   |
| <b>pH:</b>  | 7.3 - 8.5  |
| <b>Vapor pressure:</b>  | 15 mm hg (20.0 °C (68°F))  |
| <b>Boiling point/range:</b>                                       | 100 °C (212°F)   |
| <b>Melting point/ range:</b>                                      | Not available.   |
| <b>Density/Relative density:</b>                                  | 1.2702 - 1.3061 at 25 °C (77°F)  |
| <b>Relative vapor density:</b>                                    | Heavier than air   |
| <b>Flash point:</b>   | Not applicable   |
| <b>Flammable/Explosive limits - lower:</b>                        | Not available.   |
| <b>Flammable/Explosive limits - upper:</b>                        | Not available.   |
| <b>Autoignition temperature:</b>                                  | Not available.   |
| <b>Flammability:</b>  | Not applicable   |
| <b>Evaporation rate:</b>  | < 0.5 (Butyl acetate = 1)  |
| <b>Solubility:</b>  | Soluble  |
| <b>Partition coefficient n-octanol/water (logarithmic value):</b> | Not available.   |
| <b>VOC content:</b>   | 0.3 %; 42 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| <b>Dynamic viscosity:</b>   | 200,000 - 300,000 cp   |
| <b>Kinematic viscosity:</b>                                       | Not available.   |
| <b>Particle characteristics:</b>                                  | Not available.   |
| <b>Decomposition temperature:</b>                                 | Not available.   |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.   |
| <b>Hazardous reactions:</b>              | Will not occur.  |
| <b>Hazardous decomposition products:</b> | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen. |
| <b>Incompatible materials:</b>           | This product may react with oxidizing agents.  |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | Do not freeze.   |

## 11. TOXICOLOGICAL INFORMATION

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Likely routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

**Inhalation:** Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. May cause irritation to nose and throat. May cause respiratory tract irritation.

**Skin contact:** May cause skin irritation.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)                                | LD50s and LC50s  |
|---|--|
| Limestone   | None   |
| Titanium dioxide < 1% particles with diameter ≤ 10 µm | None   |
| Ethylene glycol                                       | Oral LD50 (Rat) = 5.89 g/kg<br>Oral LD50 (Mouse) = 14.6 g/kg<br>Dermal LD50 (Rabbit) = 9,530 mg/kg |
| Quartz (SiO <sub>2</sub> ), <1% respirable            | None   |

| Hazardous Component(s)                                | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects  |
|---|--------------------------|------------------------|---|
| Limestone   | Nuisance dust            |                        |   |
| Titanium dioxide < 1% particles with diameter ≤ 10 µm |                          |                        |   |
| Ethylene glycol                                       | Irritant                 |                        | Blood<br>Bone Marrow<br>Central nervous system<br>Developmental<br>Eyes<br>Kidney<br>Liver<br>Metabolic |
| Quartz (SiO <sub>2</sub> ), <1% respirable            |                          |                        | Immune system<br>Lung<br>Some evidence of carcinogenicity   |

| Hazardous Component(s)                                | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|-------------------------------|-----------------|--|
| Limestone   | No                            | No              | No                                       |
| Titanium dioxide < 1% particles with diameter ≤ 10 µm | No                            | Group 2B        | No                                       |
| Ethylene glycol                                       | No                            | No              | No                                       |
| Quartz (SiO <sub>2</sub> ), <1% respirable            | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### International Air Transportation (ICAO/IATA)

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

#### Water Transportation (IMO/IMDG)

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

## 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. This product contains one or more components with a Polymer Exemption in accordance with 40 CFR 723.250.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:  
CERCLA/SARA Section 311/312:  
CERCLA/SARA Section 313:** Please refer to the GHS classification in Section 2. This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 1, 3, 8, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 03/31/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.