



Material Safety Data Sheet

Section 1. Product and Company Identification	
Product Name	ENERGINE® SPOT REMOVER
Product Description	Not available.
Manufacturer	Reckitt Benckiser North America, Inc. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, N.J. 07054-0225
Product Identifier	Not available.
Item Number	354040
Formula Number	117-092 (F/F 354040)
UPC Number	19200-00441 (8 fl. oz. / 237 ml.)

MSDS#	Not available.
Validation Date	6/6/2006
Print Date	6/6/2006

In case of Emergency:	Telephone: 800-228-4722
Transportation Emergencies:	Chemtrec: 1-800-424-9300 (U.S. & Canada)
	Outside the U.S & Canada (North America), call: 703-527-3887

Section 2. Composition and Information on Ingredients			
Name	CAS #	% by Weight	Exposure Limits : TLV/PEL
1) NAPHTHA (PETROLEUM), LIGHT ALPHATIC	64742-89-8	100	TWA: 300 (ppm) from ACGIH (TLV) TWA: 300 STEL: 400 (ppm) from OSHA (PEL)

Section 3. Hazards Identification	
Emergency Overview	DANGER: Flammable liquid and vapor. Harmful or fatal if swallowed. May cause eye and skin irritation. Contains 100% Naphtha. KEEP OUT OF REACH OF CHILDREN.

Section 4. First Aid Measures	
Eye Contact	If in eyes, immediately flush eyes with water, remove any contact lenses, and continue to flush eyes with plenty of water for at least 15 minutes. If irritation persists, get medical attention.
Skin Contact	If on skin, remove contaminated clothing and flush skin with plenty of soap and water.
Inhalation	Move user to fresh air and maintain respiration. Call a poison center or physician immediately.
Ingestion	If swallowed, DO NOT induce vomiting. Call physician or poison control center immediately. Note to Physician: This product contains petroleum distillates. A severe lung aspiration hazard exists.

Section 5. Fire and Explosion Data	
Flammability	Flammable. See Section 14 for any Shipping Classifications.
Flash Point	CLOSED CUP: 12.778°C (55°F). (Tagliabue).
Explosive Limits in Air	Not available.
Products of Combustion	Not available.

Continued on Next Page

Fire and Explosion Hazards Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure build-up which could result in container rupture. Areas with storage of large concentration of containers exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Vapors may cause flash fire.

Fire Fighting Media and Instructions Use water fog, foam, dry chemical or CO₂. Do not use a direct stream of water. Product will float and can be reignited on surface of water.

Special Fire Fighting Instructions Wear self-contained breathing apparatus and protective clothing appropriate for fighting a chemical fire.

Section 6. Accidental Release Measures

Accidental Spill DANGER: Flammable liquid and vapor. Vapors may cause flash fire. Keep away from heat, spark, open flame, electrical motors, and outlets, pilot lights, lighted cigarettes or other ignition sources during use and until all vapors are gone. Use only with good ventilation - provide constant flow of fresh air. Take up spills with an absorbent material and place in non-leaking containers. Seal tightly for proper disposal.

Section 7. Handling and Storage

Handling and Storage DANGER: FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Contains 100% Naphtha. Do not store or use near heat, sparks or flame. Vapors may cause flash fire. Keep away from heat, sparks, open flame, electrical motors and outlets, pilot lights, lighted cigarettes or other ignition sources during use and until all vapors are gone.

Use only with good ventilation - provide constant flow of fresh air. Avoid repeated or prolonged breathing of vapors. Avoid contact with eyes or skin. Close container tightly after each use and store only with container closed. Intentional misuse by deliberately concentrating or inhaling the contents may be harmful or fatal. Repeated prolonged over-exposure to Naphtha has been associated with neurological damage. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Ventilation Requirements Use only with adequate ventilation, provide a constant flow of fresh air.

Eye Protection May cause eye irritation. Do not get in eyes. Emergency responders should wear full eye and face protection.

Skin Protection May cause skin irritation after prolonged or repeated use. Avoid skin contact. Emergency responders should wear impermeable gloves.

Respiratory Protection Avoid repeated or prolonged breathing of vapor. In case of insufficient ventilation, wear suitable respiratory equipment. Emergency responders should wear suitable respiratory protection where long term exposure to large areas of spilled liquid is possible such as a major spill, a fire or a clean-up operation.

Other Protection Emergency responders should wear impermeable clothing and footwear when responding to a situation where contact with the liquid is possible.

Work/Hygienic Practices Wash thoroughly with soap and water after handling.

Section 9. Physical and Chemical Properties

Description Thin liquid.

Odor Hydrocarbon.

pH Not available.

Color Off-white. Pale color.

Boiling/Condensation Point 129.44°C (265°F)

Specific Gravity 0.75

Vapor Pressure 26mm Hg @ 100°F

Vapor Density 3.8

Viscosity Not available.

Solubility Negligible

Physical Chemical Comments Not available.

Continued on Next Page

Section 10. Stability and Reactivity Data

Chemical Stability	The product is stable.
Conditions of Instability	Keep away from heat, spark, open flame, electrical motors, and outlets, pilot lights, lighted cigarettes or other ignition sources during use.
Incompatibility with Various Substances	Strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide and unidentified organic compounds.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information**Exposure effects**

Eye Contact	May cause eye irritation.
Skin Contact	May cause skin irritation.
Inhalation	Use only with adequate ventilation, provide a constant flow of fresh air during use. Avoid repeated or prolonged breathing of vapor. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Ingestion	Harmful or fatal if swallowed.
Carcinogenicity	Carcinogenicity: NTP: No IARC: No OSHA: No. Repeated prolonged over exposure to Naptha has been associated with neurological damage.

Section 12. Ecological Information

Ecotoxicity	Not available.
--------------------	----------------

Section 13. Disposal Considerations

Waste Disposal	Dispose of in accordance with local, state and federal regulations. None of the ingredients in this product are listed under the SARA Title III, Section 313 List of Toxic Chemicals.
-----------------------	---

Section 14. Transport Information

DOT Classification	UN1268, Petroleum distillates, n.o.s. (Naptha Petroleum) Class 3, PG II - Limited Quantity. [FP 12.778° C / 55° F, Closed Cup] Re-Classed as Consumer Commodity ORM-D.	
Proper Shipping Name	Consumer Commodity	
DOT Identification Number	Not applicable.	
Packing Group	Not applicable.	
Maritime Transportation	Not applicable.	
Hazardous Substances Reportable Quantity	Not applicable.	
Special Provisions for Transport	Not applicable.	
TDG Classification	UN1268, Petroleum distillates, n.o.s. (Naptha Petroleum) Class 3, PG II - Limited Quantity. [FP 12.778° C / 55° F, Closed Cup] Re-Classed as Consumer Commodity ORM-D.	
ADR Classification	Not applicable.	


Continued on Next Page

IMDG Classification	UN1268, Petroleum distillates, n.o.s. (Naphtha Petroleum) Class 3, PG II - Limited Quantity. [FP 12.778° C / 55° F, Closed Cup]
IATA Classification	UN1268, Petroleum distillates, n.o.s. (Naphtha Petroleum) Class 3, PG II - Limited Quantity. Or: Consumer Commodity, ID 8000.

Section 15. Regulatory Information

Federal and State Regulations	SARA Title III, Section 313 Toxic Chemical Notification & Release Reporting: None California Proposition 65: This product contains the following ingredients which require a warning under the Safe Drinking Water & Toxic Enforcement Act: None
Other Classifications	WHMIS (Canada) WHMIS CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). WHMIS CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

Section 16. Other Information

HMIS (U.S.A.)	<table border="1"> <tr> <td>Health Hazard</td> <td>2</td> </tr> <tr> <td>Fire Hazard</td> <td>3</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> <tr> <td>Personal Protection</td> <td>D</td> </tr> </table>	Health Hazard	2	Fire Hazard	3	Reactivity	0	Personal Protection	D	National Fire Protection Association (U.S.A.)	 <p>Health: 2 Fire Hazard: 3 Reactivity: 0 Specific hazard</p>
Health Hazard	2										
Fire Hazard	3										
Reactivity	0										
Personal Protection	D										
		NFPA Aerosol Level	Not applicable.								
Validated by Product Safety on 6/6/2006.		Printed 6/6/2006.									

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.