



Special Fire Fighting Procedures:  
Self contained breathing apparatus should be worn in fighting all fires involving general chemicals.  
Unusual Fire and Explosion Hazards: None

---

#### Section 5-Health Hazard Data

---

Carcinogenicity: NTP:no IARC:no OSHA regulated: no

page 2 of 3

December 21, 1999

STICK EASE SEAM ADHESIVE 209454

Overexposure--Under current OSHA criteria this product is considered non-hazardous.

#### Emergency First Aid Procedures

Eyes- Flush with water for 15 minutes, seek medical attention

Skin- Wash from skin at first opportunity.

Inhalation- No hazardous volatiles

Ingestion- Give water to drink if conscious, seek medical attention. Do not give anything by mouth to an unconscious person.

---

#### Section 6-Reactivity Data

---

This product is stable and compatible with all compounds that are compatible with water and water solutions. Hazardous polymerization does not occur.

---

#### Section 7-Precautions for Safe Handling and Use

---

Steps to be taken in case the product is released or spilled:

Small spills of 1-2 gallons or less may be diluted 50:1 with water and washed down the drain.

Large spills should be recovered as much as possible and disposed of as non-hazardous liquid waste. Consult Federal, State and Local regulations. Spilled adhesive may present a slip hazard and personnel should be cautious during cleanup.

---

#### Section 8-Control Measures

---

Respiratory protection is not usually required, however any room where this product is used should have good ventilation, i.e., open windows, exhaust fans, etc. A good, normal precaution is to wear protective gloves and glasses. No other protection equipment is necessary.

---

#### Section 9- Special Precautions

---

Store at moderate temperatures (50-100 F). Protect from freezing. Keep out of the reach of children. Keep container closed when not in use.

---

SUPPLEMENTAL INFORMATION

---

Waste Disposal

This product can handled as a non-hazardous industrial waste.

---

REGULATORY INFORMATION

---

Workplace Classifications

This product is considered non-hazardous under the OSHA Hazard Communication Standard ( 29CFR 1910.1200 ).

This product is not a "controlled product" under the Canadian Environmental Act.

page 3 of 3

December 21, 1999

STICK EASE SEAM ADHESIVE 209454

Workplace Hazardous Materials Information System (WHMIS).

---

Transportation Classifications

US DOT Shipping Class --- 60

US DOT Description --- Adhesive Paste NOI

---

Emergency Planning and Community Right to Know ( SARA Title 3 )

Section 311/312 Categorizations ( 40CFR 370 )

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

Section 313 Information (40CFR 372 )

This product does not contain a chemical which is listed in Section 313 above de minimis concentrations.

---

CERCLA Information ( 40CFR 302.4 )

Releases of this material to air, land or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation and Liability Act or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act, Title III Section 304.

---

RCRA Information

When this product becomes a waste, it is classified as a non-hazardous waste under criteria of the Resource Conservation and Recovery Act (40CFR 261).

---

Chemical Control Law Status

All components of this product are listed on the US-EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

All components of this product are listed on the Canadian Environmental Protection Act Domestic Substances List (CEPA-DSL).

---