

MATERIAL SAFETY DATA SHEET

FP101
02 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER		HMIS CODES	
FP101		Health	2
		Flammability	4
		Reactivity	0
PRODUCT NAME	DUPLI-COLOR* Filler Primer, Gray		
MANUFACTURER'S NAME	THE SHERWIN-WILLIAMS CO.		
	DUPLI-COLOR Products Group		
	Cleveland, OH 44115		
DATE OF PREPARATION	04-MAR-06	EMERGENCY TELEPHONE NO.	(216) 566-2917
		INFORMATION TELEPHONE NO.	(800) 247-3270

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
11	74-98-6	Propane		
		ACGIH TLV	2500 ppm	760 mm
		OSHA PEL	1000 ppm	
11	106-97-8	Butane		
		ACGIH TLV	800 ppm	760 mm
		OSHA PEL	800 ppm	
4	108-88-3	Toluene		
		ACGIH TLV	50 ppm (Skin)	22 mm
		OSHA PEL	100 ppm (Skin)	
		OSHA PEL	150 ppm (Skin) STEL	
1	67-63-0	2-Propanol		
		ACGIH TLV	400 ppm	33 mm
		ACGIH TLV	500 ppm STEL	
		OSHA PEL	400 ppm	
		OSHA PEL	500 ppm STEL	
27	67-64-1	Acetone		
		ACGIH TLV	500 ppm	180 mm
		ACGIH TLV	750 ppm STEL	
		OSHA PEL	1000 ppm	
15	78-93-3	Methyl Ethyl Ketone		
		ACGIH TLV	200 ppm	70 mm
		ACGIH TLV	300 ppm STEL	
		OSHA PEL	200 ppm	
		OSHA PEL	300 ppm STEL	
7	763-69-9	Ethyl 3-Ethoxypropionate		
		ACGIH TLV	Not Available	1.11 mm
		OSHA PEL	Not Available	
6	14807-96-6	Talc		
		ACGIH TLV	2 mg/m3 as Resp. Dust	
		OSHA PEL	2 mg/m3 as Resp. Dust	
2	471-34-1	Calcium Carbonate		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	15 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

Continued on page 2

```

=====
4      13463-67-7  Titanium Dioxide
                        ACGIH TLV      10  mg/m3  as Dust
                        OSHA  PEL      10  mg/m3  Total Dust
                        OSHA  PEL      5   mg/m3  Respirable Fraction
=====

```

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
Propellant < 0 F	1.0	12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

=====

SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.
Remove with inert absorbent.

=====

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

=====

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

Continued on page 4

=====

PROTECTIVE GLOVES
None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	6.89 lb/gal	825 g/l
SPECIFIC GRAVITY	0.83	
BOILING POINT	<0 - 342 F	<-18 - 172 C
MELTING POINT	Not Available	
VOLATILE VOLUME	90 %	
EVAPORATION RATE	Faster than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
Volatile Weight 50.41 %	Less Water and Federally Exempt Solvents	

=====

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable
CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

=====

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS
No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA

CAS No.	Ingredient Name				
74-98-6	Propane	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
106-97-8	Butane	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
108-88-3	Toluene	LC50	RAT	4HR	4000 ppm
		LD50	RAT		5000 mg/kg
67-63-0	2-Propanol	LC50	RAT	4HR	Not Available
		LD50	RAT		5045 mg/kg
67-64-1	Acetone	LC50	RAT	4HR	Not Available
		LD50	RAT		5800 mg/kg
78-93-3	Methyl Ethyl Ketone	LC50	RAT	4HR	Not Available
		LD50	RAT		2740 mg/kg
763-69-9	Ethyl 3-Ethoxypropionate	LC50	RAT	4HR	Not Available
		LD50	RAT		5000 mg/kg
14807-96-6	Talc	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
471-34-1	Calcium Carbonate	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
13463-67-7	Titanium Dioxide	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Continued on page 6

=====
Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene	4	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====
Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.