

MATERIAL SAFETY DATA SHEET

B58RQ5
01 00

=====
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION
=====

PRODUCT NUMBER		HMIS CODES	
B58RQ5		Health	2*
		Flammability	0
		Reactivity	0

PRODUCT NAME
ARMORSEAL* EXPRESSPATCH* Fast Dry Urethane Patch Kit (Part C), Red Aggregate

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
THE SHERWIN-WILLIAMS COMPANY	(216) 566-2917
101 Prospect Avenue N.W.	
Cleveland, OH 44115	

DATE OF PREPARATION	INFORMATION TELEPHONE NO.
05-MAR-06	(216) 566-2902

=====
Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS
=====

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
82	14808-60-7	Quartz		
		ACGIH TLV	0.05 mg/m3	as Resp. Dust
		OSHA PEL	0.1 mg/m3	as Resp. Dust
16	65997-15-1	Portland Cement		
		ACGIH TLV	10 mg/m3	as Dust
		OSHA PEL	10 mg/m3	Total Dust
		OSHA PEL	5 mg/m3	Respirable Fraction

=====
Section 3 -- HAZARDS IDENTIFICATION
=====

ROUTES OF EXPOSURE
EYE or SKIN contact with product.

EFFECTS OF OVEREXPOSURE
EYES: Causes burns.
SKIN: Causes burns.

INHALATION: Irritation of the upper respiratory system.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

=====
Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention IMMEDIATELY.

SKIN: Wash affected area thoroughly with soap and water.
If irritation persists or occurs later, get medical
attention.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

==========
Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
Not Applicable	N.A.	N.A.

FLAMMABILITY CLASSIFICATION
Not Applicable

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS
Closed containers may explode (due to the build-up of pressure) when
exposed to extreme heat.
During emergency conditions overexposure to decomposition products may
cause a health hazard. Symptoms may not be immediately apparent. Obtain
medical attention.

SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus
should be used.
Water spray may be ineffective. If water is used, fog nozzles are
preferable. Water may be used to cool closed containers to prevent
pressure build-up and possible autoignition or explosion when exposed to
extreme heat.

==========
Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove with inert absorbent.

==========
Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY
Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container closed when not in use. Transfer only to approved
containers with complete and appropriate labeling. Do not take internally.
Keep out of the reach of children.

=====
 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION
 =====

 PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

To prevent eye contact, wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin.

 =====
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES
 =====

PRODUCT WEIGHT	22.59 lb/gal	2707 g/l
SPECIFIC GRAVITY	2.72	
BOILING POINT	Not Applicable	
MELTING POINT	Not Available	
VOLATILE VOLUME	0 %	
EVAPORATION RATE	N.A.	
VAPOR DENSITY	N.A.	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
0.00 lb/gal	0 g/l	Less Water and Federally Exempt Solvents
0.00 lb/gal	0 g/l	Emitted VOC

 =====
 Section 10 -- STABILITY AND REACTIVITY
 =====

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

Continued on page 4

=====
 HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION
 Will not occur

 =====

 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

TOXICOLOGY DATA

CAS No.	Ingredient Name				
14808-60-7	Quartz	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
65997-15-1	Portland Cement	LC50	RAT	4HR	Not Available
		LD50	RAT		599.9 mg/kg

 Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

 =====

 Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 =====

 Section 14 -- TRANSPORT INFORMATION

No data available.

 =====

 Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.			

CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Continued on page 5

=====

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.