

MATERIAL SAFETY DATA SHEET

162-0616
2000

=====
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION
=====

PRODUCT NUMBER		HMIS CODES	
162-0616		Health	2
		Flammability	0
		Reactivity	0
PRODUCT NAME	PREMIUM Wallpaper Stripper		
MANUFACTURER'S NAME	THE SHERWIN-WILLIAMS COMPANY		
	101 Prospect Avenue N.W.		
	Cleveland, OH 44115		
DATE OF PREPARATION	06-MAR-06	EMERGENCY TELEPHONE NO.	(216) 566-2917
		INFORMATION TELEPHONE NO.	(216) 566-2902

=====
Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS
=====

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
2	107-98-2	1-Methoxy-2-propanol		
		ACGIH TLV	100 ppm	10.9 mm
		ACGIH TLV	150 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	150 ppm STEL	

=====
Section 3 -- HAZARDS IDENTIFICATION
=====

ROUTES OF EXPOSURE
 INHALATION of vapor or spray mist.
 EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE
 EYES: Irritation.
 SKIN: Prolonged or repeated exposure may cause irritation.
 INHALATION: Irritation of the upper respiratory system.
 In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE
 Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 None generally recognized.

CANCER INFORMATION
 For complete discussion of toxicology data refer to Section 11.

=====
Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

==========
Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT
Not Applicable

	LEL	UEL
	N.A.	N.A.

FLAMMABILITY CLASSIFICATION
Not Applicable

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS
Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.
During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used.
Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

==========
Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate the area.
Remove with inert absorbent.

==========
Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY
Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

==========
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE
Use only with adequate ventilation.
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
Wash hands after using.

=====

Continued on page 3

=====
 VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

 =====

 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	8.32 lb/gal	996 g/l
SPECIFIC GRAVITY	1.00	
BOILING POINT	212 - 255 F	100 - 123 C
MELTING POINT	Not Available	
VOLATILE VOLUME	98 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
pH	7.0	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
4.25 lb/gal	509 g/l	Less Water and Federally Exempt Solvents
0.16 lb/gal	19 g/l	Emitted VOC

 =====

 Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

 =====

 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

TOXICOLOGY DATA

CAS No.	Ingredient Name				
107-98-2	1-Methoxy-2-propanol	LC50	RAT	4HR	Not Available
		LD50	RAT		6600. mg/kg

Continued on page 4

=====
 Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

 =====
 Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 =====
 Section 14 -- TRANSPORT INFORMATION

No data available.

 =====
 Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.			

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

 =====
 Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.