



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

6401CR "StoneTech" Professional Coating Stripper
Revised 18-JUL-2005

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

StoneTech Professional, Inc.
370 North Wiget Lane
Suite 200
Walnut Creek
California
94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:
703-527-3887
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
*n-Methylpyrrolidone	872-50-4	<70
Dibasic Esters		<15
Water	7732-18-5	<10
Tripropylene Glycol Methyl Ether	25498-49-1	<7
*Ethylene Glycol Mono-n-butyl Ether	111-76-2	<7

* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation: May cause respiratory irritation.
Skin Contact: May cause severe skin irritation.
Eye Contact: May cause severe eye irritation.
Ingestion: Ingestion may be harmful or fatal.

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

(HAZARDS IDENTIFICATION - Continued)

Material
Ethylene Glycol Mono-n-butyl Ether

IARC NTP OSHA ACGIH
A3

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

In case of contact, immediately flush skin with plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Call a physician. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : >150 F (>66 C)
Method : Closed Cup.

Hazardous gases/vapors produced in fire are carbon monoxide, carbon dioxide, oxides of nitrogen.

Extinguishing Media

CO2, Dry Chemical.

Do NOT use direct water stream.

(FIRE FIGHTING MEASURES - Continued)

Fire Fighting Instructions

Wear self-contained breathing apparatus (SCBA) and full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

Initial Containment

Dike spill.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material.

HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Store out of reach of children.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures. Avoid exposure to moisture.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

n-Methylpyrrolidone

PEL (OSHA)	: None Established
TLV (ACGIH)	: None Established
AEL * (DuPont)	: 5 ppm, 8 & 12 Hr. TWA, Skin
WEEL (AIHA)	: 10 ppm, 8 Hr. TWA, Skin

Ethylene Glycol Mono-n-butyl Ether

PEL (OSHA)	: 50 ppm, 240 mg/m ³ , 8 Hr. TWA, Skin
TLV (ACGIH)	: 20 ppm, 8 Hr. TWA, A3
AEL * (DuPont)	: 5 ppm, 8 Hr. TWA, Skin

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Vapor Pressure	: 0.2 mm Hg
Odor	: (mild), Amine.
Form	: Liquid.
Color	: Colorless.
Specific Gravity	: 1.03

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

Incompatible or can react with acids, strong oxidizers.

Decomposition

Thermal decomposition may produce carbon dioxide, carbon monoxide.

DISPOSAL CONSIDERATIONS

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION

Shipping Information

Not Regulated as a hazardous material by DOT, IMO, or IATA.

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : Listed.

State Regulations (U.S.)

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm: N-Methylpyrrolidone

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS