



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

"StoneTech" Professional Heavy Duty Exterior Sealer
6471CR Revised 23-JAN-2006

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

StoneTech Professional, Inc.
370 North Wiget Lane
Suite 200
Walnut Creek
California
94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:
703-527-3887
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

Components

| Material | CAS Number | % |
|---------------------------------|------------|----|
| Aliphatic Petroleum Distillates | 64742-88-7 | 94 |
| Proprietary Silicone Resin | | <6 |

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation: Inhalation of large amounts of respirable particles may be toxic to the lungs.

Skin Contact: May cause skin irritation with discomfort and rash.

Eye Contact: May cause eye irritation with discomfort, tearing or blurring of vision.

Ingestion: Repeated ingestion of large amounts may cause liver damage. Harmful or fatal if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : 104 F (40 C)

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Initial Containment

Dike spill.

Spill Clean Up

Dispose of in an approved container.

HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

(EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Exposure Limits

"StoneTech" Professional Heavy Duty Exterior Sealer
PEL (OSHA) : None Established
TLV (ACGIH) : None Established

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Evaporation Rate : <1 (Butyl Acetate=1.0)
Odor : (mild).
Form : Liquid.
Color : Colorless.
Specific Gravity : 1

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

Incompatible or can react with water or acids to release methanol.

Decomposition

Hazardous decomposition products may include methanol, carbon dioxide, carbon monoxide, and hydrogen fluoride.

Polymerization

Polymerization will not occur.

DISPOSAL CONSIDERATIONS

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION

Shipping Information

DOT: Not Regulated by DOT in packages with a capacity of less than 119 gallons.

IMDG:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid

For 2 Oz., 1 Quart, and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid
Special Instructions : Liquid Quantity

IATA:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid

For 1 Quart and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid
Special Instructions : Limited Quantity

For 2 Oz.:

Proper Shipping Name : Consumer Commodity
Hazard Class : 9
UN Number : ID 8000
Label : Miscellaneous

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : Listed.

OTHER INFORMATION

NFPA, NPCA-HMIS

NPCA-HMIS Rating
Health : 2
Flammability : 2
Reactivity : 0

Personal Protection rating to be supplied by user depending on use conditions.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS