



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

"StoneTech" Professional Enhancer
6410CR Revised 14-JUN-2005

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

StoneTech Professional, Inc.
370 North Wiget Lane
Suite 200
Walnut Creek
California
94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:
703-527-3887
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
Fluorinated Acrylic Copolymer		
*Ethylene Glycol Mono-n-butyl Ether	111-76-2	<5
Modified Linseed Oil		
Water	7732-18-5	>75

* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation: May cause respiratory irritation with headaches, dizziness, nausea, unconsciousness.

Skin Contact: May cause severe skin irritation.

Eye Contact: May cause severe eye irritation.

Ingestion: May irritate stomach and intestines. Prolonged/repeated exposure by ingestion may be harmful or fatal.

(HAZARDS IDENTIFICATION - Continued)

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

Material	IARC	NTP	OSHA	ACGIH
Ethylene Glycol Mono-n-butyl Ether				A3

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : >230 F (>110 C)
Method : Closed Cup.

Not a fire or explosion hazard.

Extinguishing Media

Use media appropriate for surrounding material.

(FIRE FIGHTING MEASURES - Continued)

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

ACCIDENTAL RELEASE MEASURES-----
Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Initial Containment

Dike spill.

Spill Clean Up

Dispose of in an approved container.

HANDLING AND STORAGE-----
Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures.

EXPOSURE CONTROLS/PERSONAL PROTECTION-----
Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

(EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

Ethylene Glycol Mono-n-butyl Ether

PEL (OSHA)	: 50 ppm, 240 mg/m ³ , 8 Hr. TWA, Skin
TLV (ACGIH)	: 20 ppm, 8 Hr. TWA, A3
AEL * (DuPont)	: 5 ppm, 8 Hr. TWA, Skin

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Evaporation Rate	: >1 (Butyl Acetate=1.0)
Solubility in Water	: Soluble
pH	: 4.5
Odor	: (mild), Pungent.
Form	: Liquid.
Color	: Milky, White.
Specific Gravity	: 0.9997

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

Incompatible or can react with strong oxidizers, alkalies.

Decomposition

Hazardous gases or vapors can be released, including carbon dioxide, carbon monoxide, hydrogen fluoride (HF).

Polymerization

Polymerization will not occur.

DISPOSAL CONSIDERATIONS
-----**Waste Disposal**

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION
-----**Shipping Information**

Not Regulated as a hazardous material by DOT, IMO, or IATA.

REGULATORY INFORMATION
-----**U.S. Federal Regulations**

TSCA Inventory Status : Listed.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS