

The Valvoline Company

Date Prepared: 01/14/02

MSDS No: 503.0177220-001.012I

PYROIL WINDSHIELD WASHER CONC 1/5 GA

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL WINDSHIELD WASHER CONC 1/5 GA

General or Generic ID: SOLVENT BLEND

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by volume)
METHYL ALCOHOL	67-56-1	99.6

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing this material may be harmful.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), visual impairment (including blindness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: cardiac abnormalities, liver abnormalities, spleen damage, nervous system damage, eye damage, kidney damage, lung damage, brain damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these

organs: eye damage, visual impairment.

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

50.0 - 60.0 F (10.0 - 15.5 C) TCC

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide.

Fire and Explosion Hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

alcohol foam, water fog.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 3, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage
Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection
Not required under normal conditions of use.

Skin Protection
Not required under normal conditions of use. Other protective
equipment: not required under normal conditions of use.

Respiratory Protections
Not required under normal conditions of use.

Engineering Controls
Not required under normal conditions of use.

Exposure Guidelines
Component

METHYL ALCOHOL (67-56-1)
OSHA VPEL 200.000 ppm - TWA ((Skin))
OSHA VPEL 250.000 ppm - STEL ((Skin))
ACGIH TLV 200.000 ppm - TWA ((Skin))
ACGIH TLV 250.000 ppm - STEL ((Skin))

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
No data

Vapor Pressure
No data

Specific Vapor Density
No data

Specific Gravity
.790 - .801 @ 77.00 F

Liquid Density
6.640 lbs/gal @ 77.00 F
.795 kg/l @ 25.00 C

Percent Volatiles (Including Water)
No data

Evaporation Rate
SLOWER THAN ETHYL ETHER

Appearance
CLEAR

State
LIQUID

Physical Form

No data

Color

BLUE

Odor

No data

pH

Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

FLAMMABLE LIQUIDS, N.O.S., 3, UN 1993, II

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

METHANOL

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

5039 METHANOL

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component	Component
METHYL ALCOHOL	5000

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number
METHANOL	67-56-1

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

METHYL ALCOHOL	67-56-1
----------------	---------

Pennsylvania RTK Label Information

METHANOL	67-56-1
----------	---------

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page