

The Valvoline Company

Date Prepared: 01/14/02

MSDS No: 503.0253095-002.014I

PYROIL NON-CHLOR BRAKE PARTS CLNR 1/5 GA

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL NON-CHLOR BRAKE PARTS CLNR 1/5 GA

General or Generic ID: AUTOMOTIVE CHEMICAL

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by volume)
TOLUENE	108-88-3	45.0
METHYL ALCOHOL	67-56-1	30.0
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	20.0- 30.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Additional symptoms of eye exposure may include: blurred vision.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: liver abnormalities, anemia, spleen damage, nervous

system damage, eye damage, kidney damage, lung damage, brain damage, effects on hearing, central nervous system damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: liver abnormalities, eye damage, visual impairment.

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be

aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

20.0 F (-6.6 C) TCC

Explosive Limit

(for component) Lower 1.2 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 2, Flammability - 3, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Other protective equipment: not required under normal conditions of use. Wear resistant gloves such as: neoprene.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

TOLUENE (108-88-3)

OSHA VPEL 100.000 ppm - TWA

OSHA VPEL 150.000 ppm - STEL

ACGIH TLV 50.000 ppm - TWA ((Skin))

ACGIH TLV 150.000 ppm - STEL ((Skin))

METHYL ALCOHOL (67-56-1)

OSHA VPEL 200.000 ppm - TWA ((Skin))

OSHA VPEL 250.000 ppm - STEL ((Skin))

ACGIH TLV 200.000 ppm - TWA ((Skin))

ACGIH TLV 250.000 ppm - STEL ((Skin))

ALIPHATIC PETROLEUM DISTILLATES (64742-89-8)

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
(for component) 147.0 F (63.8 C) @ 760 mmHg

Vapor Pressure
(for component) 97.680 mmHg @ 68.00 F

Specific Vapor Density
> 1.000 @ AIR=1

Specific Gravity
.803 - .809 @ 60.00 F

Liquid Density
6.711 lbs/gal @ 60.00 F
.806 kg/l @ 15.60 C

Percent Volatiles (Including Water)
No data

Evaporation Rate
SLOWER THAN ETHYL ETHER

Appearance
CLEAR

State
LIQUID

Physical Form
No data

Color
CLEAR, COLORLESS

Odor
No data

pH
Not applicable

Flame Propagation
> 18.000 in

10. STABILITY AND REACTIVITY

Hazardous Polymerization
Product will not undergo hazardous polymerization.

Hazardous Decomposition
May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability
Stable. Avoid heat, open flame, and prolonged storage at elevated temperatures.

Incompatibility
Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

PAINT RELATED MATERIAL,3,UN1263,II

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

TOLUENE

PETROLEUM NAPHTHA

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

2066 TOLUENE
16954 METHANOL

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component

Component

TOLUENE 1000
METHYL ALCOHOL 5000

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)

CAS Number

TOLUENE 108-88-3

METHANOL

67-56-1

International Regulations
Inventory Status
Not determined

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.
TOLUENE

New Jersey RTK Label Information

TOLUENE	108-88-3
METHYL ALCOHOL	67-56-1
NAPHTHA, SOLVENT	64742-89-8

Pennsylvania RTK Label Information

BENZENE, METHYL-	108-88-3
METHANOL	67-56-1

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page