



Meguiar's USA
17991 Mitchell South
Irvine, CA 92614
Tel: 949-752-8000
Fax: 949-752-5784

In case of **emergency or spill**, contact CHEMTREC at 800-424-9300

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: A1214 - Car Cleaner Wax-Paste

Print date: 03/21/2005

Reference Number: 18-87E

Prepared Date: 03/21/2005

Use of the Substance/Preparation

Recommended use: Wax emulsion.

Company/Undertaking Identification

Meguiar's Holland
Laan der Verenigde Naties 40
33174 DA Dordrecht
Holland
Tel: 31-78-6210268

Meguiar's Hong Kong
Suite 6-7, 20/F Marina House
68 Hing Man Street
Shaukeiwan
Hong Kong
Tel: 852-2967-0202

Meguiar's France
79 avenue Edouard Vaillant
92100 BOULOGNE
France
Tel: 33-1-46-10-47-81

Meguiar's UK Ltd.
14 Cottesbrooke Park
Heartlands
Daventry NN11 5YL
Tel: 0870 241 6696
Fax: 01327 300 116

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature of the preparation

Components	CAS #	% Weight	OSHA PEL TWA	EINECS No.	Classification
Heavy Alkylate Naphtha	64741-65-7	55-70	None	265-067-2	Xn; R65
Calcined Kaolin Clay	66402-68-4	2-10	10mg/m ³	266-340-9	Xi; R38
Kaolin	1332-58-7	1-5	10mg/m ³	---	R42
Isoparaffinic Hydrocarbon	64742-47-8	1-5	None	265-149-8	---

3. HAZARDS IDENTIFICATION

Most important hazards: Combustible material. This product contains chemicals listed on Canada WHMIS. See Section 15.

4. FIRST AID MEASURES

General Advice: In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Inhalation: Prolonged or intentional exposure to high concentrations may cause respiratory track irritation. Move to fresh air. If symptoms persist, call a physician.

Skin contact:	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.
Eye contact:	Flush eyes with water as a precaution. If symptoms persist, call a physician
Ingestion:	Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting. Consult a physician if necessary.

5. FIRE-FIGHTING MEASURES

NFPA:

Health: 1

Flammability: 2

Reactivity: 0

Suitable extinguishing media:

Use dry chemical, CO₂, water spray or alcohol-resistant foam.

Specific hazards:

Not applicable

Special protective equipment for firefighters:

In the event of fire, wear self-contained breathing apparatus.

Extinguishing media which must not be used for safety reasons:

Not applicable

Specific methods:

Not applicable

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Ensure adequate ventilation. Avoid contact with skin and eyes

Environmental precautions:

Local authorities should be advised if significant spillages cannot be contained. Do not contaminate surface water. Prevent further leakage or spillage.

Methods for cleaning up:

Wipe up with absorbent material (e.g. cloth, fleece).

7. HANDLING AND STORAGE

Handling:

Technical measures/precautions:

Use only in area well ventilated area.

Safe handling advice:

Keep away from heat and sources of ignition.. Do not smoke.. Take measures to prevent the build up of electrostatic charge.

Storage:

Keep product and empty container away from heat and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Do not freeze. Keep away from direct sunlight.

Incompatible products:

Do not store together with acids or oxidizers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:	Ensure adequate ventilation..
Respiratory protection:	No personal respiratory protective equipment normally required.
Skin and body protection:	No special precautions required..
Eye protection:	Avoid contact with eyes. If splashes are likely to occur, wear: Goggles
Hand protection:	Preventive skin protection: Neoprene Gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Appearance:	Paste	Physical state:	Paste
Color:	Light cream	Odor:	Hydrocarbon-like

Important Health Safety and Environmental Information

pH @70° F:	N/A	Method:	PMCC-ASTM D93-90
Flash point:	150 (°F), 66 (°C)		
Boiling point/range:	365 (°F), 185 (°C)		
Water Solubility:	Insoluble		
Vapor density:	>1		
Evaporation rate:	<1		
VOC content:	65% max.		
Specific gravity:	0.86		

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Polymerization:	None under normal processing.
Conditions to avoid:	Extremes of temperature and direct sunlight
Materials to avoid:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials..
Hazardous decomposition products:	None under normal use

11. TOXICOLOGICAL INFORMATION

Component Information

Additional Information:	The product is not subject to classification according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
--------------------------------	---

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product Information

Aquatic toxicity: No information available

Component Information

Ecotoxicity effects: Not determined

Components	Ecotoxicity - Freshwater Algae	Exotoxicity - Microtox
Calcined Kaolin Clay 66402-68-4	= 30 ug/L 96 Hr EC50 freshwater algae (Selenastrum capricornutum)	

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

Contaminated packaging:

Disposal must be made according to local and federal regulations.

Ewc waste disposal no:

Not applicable

Further information

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific

14. TRANSPORT INFORMATION

General Transportation Statement

- This product does not require classification by DOT, IATA, ICAO or IMDG.

Other information:

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements and mode-specific or quantity-specific shipping requirements.

15. REGULATORY INFORMATION

Components	TSCA	DSL/NDSL	Canada - WHMIS Classification
Calcined Kaolin Clay 66402-68-4	Present	Present	B4;D2B
Kaolin 1332-58-7			D2B
Isoparaffinic Hydrocarbon 64742-47-8	Present	Present	

CERCLA/SARA 313 Emission reporting

None

16. OTHER INFORMATION

Prepared by: Health & Safety
Literary reference: None

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist

End of Safety Data Sheet