

MATERIAL SAFETY DATA SHEET



**SECTION 1 - PRODUCT AND COMPANY INFORMATION**

PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

**EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)**  
(24 hours/day):

(514) 645-1320 (Canada)  
01-800-00-21-400 (Mexico)  
0532-83889090 (China)

**TECHNICAL INFORMATION:** 1-800-441-9695 (8:00 am to 5:00 pm EST)

**PRODUCT SAFETY/MSDS INFORMATION:** (412) 492-5555 7:00 a.m. - 4:30 p.m. EST

**Product ID:** 72102 (0822)  
**PRODUCT NAME:** OLYMPIC INTERIOR SATIN WH  
**SYNONYMS:** None  
**ISSUE DATE:** 08/22/2007  
**EDITION NO.:** 4  
**CHEMICAL FAMILY:** Acrylic

**EMERGENCY OVERVIEW:**  
CAUSES EYE IRRITATION. MAY CAUSE SLIGHT SKIN IRRITATION. VAPOR AND/OR SPRAY MIST MAY BE HARMFUL IF INHALED. MAY BE HARMFUL IF SWALLOWED. This product is not expected to present any unusual hazards under fire or spill conditions. Read entire MSDS before use.

**SECTION 2 - COMPOSITION INFORMATION**

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

Material/ CAS Number	Percent	Hazardous	
TITANIUM DIOXIDE 13463-67-7	10 - 30	X	
SODIUM POTASSIUM ALUMINUM SILICATE 37244-96-5	1 - 5	X	
SILICA 7631-86-9	1 - 5	X	
PROPRIETARY Proprietary	0.5-1.5	X	
SILICA CRISTOBALLITE 14464-46-1	0.1-1.0	X	
(As Silica, crystalline and Quartz) 14464-46-1	*	X	See Sections 8 and 15 for information.
(As Nuisance Particulates) 37244-96-5	*	X	See Sections 8 and 15 for information.

**SECTION 3 - HAZARDS IDENTIFICATION**

**ACUTE OVEREXPOSURE EFFECTS**

**EYE CONTACT:**  
Causes eye irritation. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

**SKIN CONTACT:**  
May cause slight skin irritation. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

**SKIN ABSORPTION:**  
Skin absorption not expected to occur.

**INHALATION:**  
Vapor and/or spray mist may be harmful if inhaled.

**INGESTION:**

May be harmful if swallowed.

**SIGNS & SYMPTOMS OF OVEREXPOSURE:**

Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Not applicable.

**CHRONIC OVEREXPOSURE EFFECTS**

Avoid long-term and repeated contact.

This product contains crystalline silica which has been classified as a human carcinogen by IARC. Long-term exposures may also lead to a disabling lung condition known as silicosis. The risk depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Use of appropriate personal protective equipment and/or engineering controls should be employed whenever these types of operations are being performed.

The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

**SECTION 4 - FIRST AID MEASURES**

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

**EYE CONTACT:**

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

**SKIN CONTACT:**

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact a poison control center, emergency room, or physician as further treatment may be necessary.

**INHALATION:**

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

**INGESTION:**

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

**SECTION 5 - FIRE FIGHTING MEASURES**

**FLAMMABLE PROPERTIES**

**FLASHPOINT:** >200 Degrees F (> 93 Degrees C)

**FLASHPOINT TEST METHOD:**

Pensky-Martens Closed Cup

**UEL:** Not Available.

**LEL:** Not Available.

**AUTOIGNITION TEMPERATURE:**

Not Available.

**EXTINGUISHING MEDIA:**

Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical or universal aqueous film forming foam) designed to extinguish NFPA Class IIIB combustible liquid fires.

**PROTECTION OF FIREFIGHTERS:**

Water spray may be ineffective. Water spray may be used to cool closed containers that are exposed to extreme heat. If water is used, fog nozzles are preferable. Firefighters should wear self-contained breathing apparatus and full protective clothing.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Closed containers may explode or burst (due to the build-up of steam pressure) when exposed to extreme heat. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

**SECTION 6 - ACCIDENTAL RELEASE MEASURE**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

**SECTION 7 - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:**

If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

**STORAGE:**

Protect from freezing.

**SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION**

**ENGINEERING CONTROLS:**

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES:**

Wear safety glasses with side shields.

**SKIN/GLOVES:**

Wear protective clothing. Gloves should be constructed of: neoprene rubber or nitrile rubber. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. Clean contaminated clothing and shoes.

**RESPIRATOR:**

Where ventilation is inadequate, use a NIOSH- approved air purifying respirator with the appropriate chemical cartridges or positive- pressure, air-supplied respirator. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS**

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

Material/ CAS Number	Percent	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
TITANIUM DIOXIDE 13463-67-7	10 - 30	10 mg/m <sup>3</sup>	Not established	10 mg/m <sup>3</sup>	Not established
SODIUM POTASSIUM ALUMINUM SILICATE 37244-96-5	1 - 5	10 MG/m <sup>3</sup>	Not established	Not established	Not established
SILICA 7631-86-9	1 - 5	10 mg/m <sup>3</sup>	Not established	6 mg/m <sup>3</sup>	Not established
PROPRIETARY Proprietary	0.5-1.5	10MG/m <sup>3</sup>	Not established	R- 5MG/m <sup>3</sup>	Not established
SILICA CRISTOBALLITE 14464-46-1	0.1-1.0	R- 0.025 MG/m <sup>3</sup>	Not established	R- 0.05 mg/m <sup>3</sup>	Not established
(As Nuisance Particulates) 37244-96-5	*	R- 3 MG/m <sup>3</sup>	Not established	R- 5 mg/m <sup>3</sup>	Not established

Material/ CAS Number	Percent	Ontario TWA	Ontario STEL	PPG IPEL	PPG STEL
TITANIUM DIOXIDE 13463-67-7	10 - 30	10 MG/m <sup>3</sup>	Not established	Not established	Not established
SODIUM POTASSIUM ALUMINUM SILICATE 37244-96-5	1 - 5	10 MG/m <sup>3</sup>	Not established	Not established	Not established
SILICA 7631-86-9	1 - 5	R- 0.10 MG/m <sup>3</sup>	Not established	Not established	Not established
SILICA CRISTOBALLITE 14464-46-1	0.1-1.0	0.05 MG/m <sup>3</sup>	Not established	Not established	Not established
(As Nuisance Particulates) 37244-96-5	*	R- 3 MG/m <sup>3</sup>	Not established	Not established	Not established

**Key:** ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit (1989 Vacated values); IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S-Potential Skin Absorption; R-Respirable Dust]  
**Additional Information** Not applicable.

**SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES  
(FORMULA VALUES, NOT SALES SPECIFICATIONS)**

<b>SPECIFIC GRAVITY:</b>	1.226
<b>PHYSICAL STATE:</b>	Liquid
<b>Percent Solids:</b>	41.98
<b>Percent Volatile by Volume:</b>	70.640
<b>pH:</b>	Not available.
<b>ODOR THRESHOLD:</b>	Not available.
<b>Vapour Pressure:</b>	17.5 mmHg
<b>ODOR/APPEARANCE:</b>	Viscous liquid with an odor characteristic of the chemical family and any solvents listed in Section 2.
<b>VAPOR DENSITY:</b>	HEAVIER THAN AIR
<b>Evaporation Rate:</b>	36
<b>BOILING POINT OR RANGE:</b>	212 - 212Degrees F
<b>Freezing Point or Range:</b>	Not Applicable.
<b>Melting Point or Range(°C):</b>	Not Applicable.
<b>Partition coefficient (n-octanol/water):</b>	Not Applicable.
<b>WEIGHT PER GALLON:</b>	10.22 (U.S.) / 12.2 (IMPERIAL)

**SECTION 10 - STABILITY AND REACTIVITY**

**STABILITY:**

This product is normally stable and will not undergo hazardous reactions.

**CONDITIONS TO AVOID:**

None Known.

**INCOMPATIBLE MATERIALS:**

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

**HAZARDOUS POLYMERIZATION:**

None Known.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

- Carbon monoxide - Carbon dioxide - Oxides of aluminum - Lower molecular weight polymer fractions

Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

**SECTION 14 - TRANSPORTATION INFORMATION**

**Proper Shipping Name:** Paint- Non-Regulated Goods  
**NOS Technical Name:** None  
**Hazard Class:** None  
**Subsidiary Class(es):** None  
**UN Number:** None  
**Packing Group:** None

**SECTION 11 - TOXICOLOGICAL INFORMATION**

**ACUTE TOXICITY**

Material/ CAS Number	Percent	ORAL LD50 (g/kg)	DERMAL LD50 (g/kg)	INHALATION LC50 (mg/l)
TITANIUM DIOXIDE 13463-67-7	10 - 30	10.00 g/kg	Not Available	Not Available

**USA - RQ Hazardous Substances:** None  
**USA-RQ Hazardous Substance** None  
**Threshold Ship Weight:**  
**Marine Pollutant Name:** None

**SECTION 15 - REGULATORY INFORMATION**

**INVENTORY STATUS**

**U.S. TSCA:** This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

**FEDERAL REGULATIONS**

**US Regulations**

Material/ CAS Number	Percent	CERCLA HS -	SARA EHS-	SARA 313
		RQ (LBS)	TPQ (LBS)	
TITANIUM DIOXIDE 13463-67-7	10 - 30	Not Listed	Not Listed	Not Listed
SODIUM POTASSIUM ALUMINUM SILICATE 37244-96-5	1 - 5	Not Listed	Not Listed	Not Listed
SILICA 7631-86-9	1 - 5	Not Listed	Not Listed	Not Listed
PROPRIETARY Proprietary	0.5-1.5	Not Listed	Not Listed	Not Listed
SILICA CRISTOBALLITE 14464-46-1	0.1-1.0	Not Listed	Not Listed	Not Listed

**CHRONIC TOXICITY**

**Ingredient Target Organ/Chronic Effects:**

- Carcinogen - Lung

**Mutagenicity Toxicity:**

This has not been tested for this product.

**Reproductive Toxicity:**

This has not been tested for this product.

**SUPPLEMENTAL HEALTH INFORMATION:**

Material/ CAS Number	Percent	Ingredient Specific Animal Data:
TITANIUM DIOXIDE 13463-67-7	10 - 30	This product contains titanium dioxide. Animals inhaling massive quantities of titanium dioxide dust in a long-term study developed lung tumors. Studies with humans involved in manufacture of this pigment indicate no increased risk of cancer from exposure.

**SECTION 12 - ECOLOGICAL INFORMATION**

**POTENTIAL ENVIRONMENTAL EFFECTS**

**Ecotoxicity:** No Information Available.

**ENVIRONMENTAL FATE**

**Mobility:** No information available.

**Biodegradation:** No information available.

**Bioaccumulation:** No Information Available.

**SARA 311/312**

Health (acute): No

Health (chronic): Yes

Fire (flammable): No

Pressure: No

Reactivity: No

**WHMIS HAZARD CLASS:** - Class D, Division 2, Subdivision A

**PHYSICAL/CHEMICAL**

**Hydrolysis:** No information available.

**Photolysis:** No information available.

**STATE/PROVINCIAL REGULATIONS**

**CALIFORNIA PROP. 65:** WARNING: This product contains a chemical known to the State of California to cause cancer.

**Additional Information**

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal.

Material/ CAS Number	Percent	IARC Group 1(Kno wn Human Carc.)	IARC Group 2A (Proba ble Carc.)	IARC 2B (Suspec ted Carc.)	ACGIH Carc.	NTP Known Carc.	OSHA Carc.
TITANIUM DIOXIDE 13463-67-7	10 - 30	N	N	Y	N	N	N
SILICA CRISTOBALLITE 14464-46-1	0.1-1.0	Y	N	N	N	N	N

**Key:** IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program \*Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

**SECTION 16 - OTHER INFORMATION**

**Hazard Rating Systems**

**NFPA Rating:** 1 10

**HMIS Rating:** 1\*10

**Rating System:** 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, \*=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire Protection Association;

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

**PREPARED BY:** Product Safety Department

**REASON FOR REVISION:** Section 9 has been updated. Date. Edition. Updated MSDS format.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200), the supplier notification requirements of SARA Title III, Section 313 and other applicable right-to-know regulations.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

72102 000045 (00477392.001)(08/21/07)  
070821, 000, 0822

\*\*\* END OF MSDS \*\*\*