

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**CROWN CAMP FUEL**  
**NEW MSDS DATE:** 11/28/2001

**DATE:** 11/28/01  
**PAGE 1 OF 7**

### **MATERIAL SAFETY DATA SHEET**

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1.  
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)  
IMPORTANT: Read this MSDS before handling & disposing of this product.  
Pass this information on to employees, customers, & users of this product.

#### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY**

**PRODUCT IDENTITY:** **CROWN CAMP FUEL**  
**COMPANY IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**COMPANY ADDRESS:** 1904 MYKAWA / P O BOX 875  
**COMPANY CITY:** PEARLAND, TX 77588-0875  
**COMPANY PHONE:** 1-281-485-1457  
**CHEMTREC PHONE:** 1-800-424-9300

#### **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

**CONTAINS:**

95-100% LIGHT HYDROTREATED DIST (68410-97-9)  
Number in parentheses is CAS #, number in brackets is European EC #.

LF0001COLE01

#### **SECTION 3. HAZARDS IDENTIFICATION**

**RISK STATEMENTS:**

R12 Extremely Flammable.  
R18 In use may form flammable/explosive vapor-air mixture.  
R65 Harmful: may cause lung damage if swallowed.

**SAFETY STATEMENTS:**

S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition. No smoking.

**PRODUCT IDENTITY:** PACKAGING SERVICE CO., INC.  
**NEW MSDS DATE:** 11/28/2001  
**CROWN CAMP FUEL**

**DATE:** 11/28/01  
**PAGE 2 OF 7**

#### **SECTION 4. FIRST AID MEASURES**

**EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.

**SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

**INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

**SWALLOWING:**

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting. Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal.

LF0001COLE01

#### **SECTION 5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:**

NFPA Class B extinguishers (Carbon Dioxide or foam) for Class I B liquid fires.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Water spray may be ineffective on fire but can protect fire fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES:**

**EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**

Keep container tightly closed. Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

**CONTAINMENT TECHNIQUES:**

Stop spill at source. Dike area & contain.

**CLEAN-UP PROCEDURES:**

Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

**OTHER PRECAUTIONS**

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**NEW MSDS DATE:** 11/28/2001 **CROWN CAMP FUEL**

**DATE:** 11/28/01  
**PAGE 3 OF 7**

## **SECTION 7. HANDLING AND STORAGE**

### **HANDLING:**

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

### **STORAGE:**

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone. Do not store above 49 C/120 F. Store large amounts in structures made for OSHA Class I B liquids. Keep container tightly closed & upright when not in use to prevent leakage.

LF0001COLE01

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:**

### **EXPOSURE CONTROLS:**

Use vapor, mist gas mask within use limits, or ventilate to keep vapors of this material below 300 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.

### **VENTILATION:**

LOCAL EXHAUST	: Necessary
MECHANICAL (GENERAL)	: Acceptable
SPECIAL	: None
OTHER	: None

### **PERSONAL PROTECTIONS:**

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

### **WORK & HYGIENIC PRACTICES:**

Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

**PACKAGING SERVICE CO., INC.**  
**PRODUCT IDENTITY: CROWN CAMP FUEL**  
**NEW MSDS DATE: 11/28/2001**

**DATE: 11/28/01**  
**PAGE 4 OF 7**

#### SECTION 9. PHYSICAL DATA

APPEARANCE:	Liquid, Water-White
ODOR:	Mild
BOILING RANGE:	52 110 137 C / 125 231 280 F
AUTO IGNITION TEMPERATURE:	321 C / 610 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	1.9
FLASH POINT (TEST METHOD):	-18 C / -2 F (TCC)
FLAMMABILITY CLASSIFICATION:	Class I B
GRAVITY @ 60 F:	
API:	70.6
SPECIFIC GRAVITY (Water=1):	.700
POUNDS/GALLON:	5.831
VOC'S (>0.44 Lbs/Sq In):	100.1 Vol. % / 700.8 g/L / 5.837 Lbs/Gal
TOTAL VOC'S (TVOC):	100.0 Vol. % / 700.0 g/L / 5.831 Lbs/Gal
NONEXEMPT VOC'S (CVOC):	100.0 Vol. % / 700.0 g/L / 5.831 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	0.0 Wt. % / 0.0 g/L / 0.000 Lbs/Gal
VAPOR PRESSURE (mm of Hg)@20 C	150.0
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	150.0
VAPOR DENSITY (air=1):	2.4
WATER ABSORPTION:	Negligible
REFRACTIVE INDEX:	1.357

#### SECTION 10. STABILITY & REACTIVITY

**STABILITY:**

Stable

**CONDITIONS TO AVOID:**

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

**MATERIALS TO AVOID:**

Isolate from strong oxidizers such as permanganates, chromates & peroxides.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon Monoxide, Carbon Dioxide from burning.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

LF0001COLE01

#### SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
Light Hydrotreated Dist	68410-97-9	1000 ppm	600 ppm	No
This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.				

**PRODUCT IDENTITY:** PACKAGING SERVICE CO., INC.  
**NEW MSDS DATE:** 11/28/2001  
**CROWN CAMP FUEL**

**DATE:** 11/28/01  
**PAGE 5 OF 7**

LF0001COLE01

**SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)**

<b>MATERIAL</b>	<b>CAS #</b>	<b>CEILING</b>	<b>STEL (OSHA/ACGIH)</b>
	None Known	None Known	

**ACUTE HAZARDS**

**EYE & SKIN CONTACT:**

Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

**INHALATION:**

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

**SWALLOWING:**

Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

**SUBCHRONIC HAZARDS/CONDITIONS AGGREGATED  
CONDITIONS AGGREGATED**

Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS**

**CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

Leukemia been reported in humans from Benzene. This product contains less than 100 ppm of Benzene. Not considered hazardous in such low concentrations. Absorption thru skin may be harmful.

**PACKAGING SERVICE CO., INC.**  
**PRODUCT IDENTITY: CROWN CAMP FUEL**  
**NEW MSDS DATE: 11/28/2001**

**DATE: 11/28/01**  
**PAGE 6 OF 7**

## **SECTION 12. ECOLOGICAL INFORMATION**

### **MAMMALIAN INFORMATION:**

No mammalian information is available on this product.

### **AQUATIC ANIMAL INFORMATION:**

No aquatic environmental information is available on this product.

### **MOBILITY:**

This material is a mobile liquid.

### **DEGRADABILITY:**

This product is non-biodegradable.

### **ACCUMULATION:**

This product does not accumulate or bio-magnify in the environment.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If questions exist, contact the appropriate agencies.

## **SECTION 14. TRANSPORT INFORMATION**

DOT SHIPPING NAME: Petroleum Distillates, n.o.s., 3,UN1268, PG-II

Limited quantities per 49CFR 173.150(b) and (c) may be renamed as "Consumer Commodity" and reclassified as ORM-D

DRUM LABEL: (FLAMMABLE LIQUID)

IATA / ICAO: Petroleum Distillates, n.o.s., 3,UN1268, PG-II

IMO / IMDG: Petroleum Distillates, n.o.s., 3,UN1268, PG-II

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

LF0001COLE01

## **SECTION 15. REGULATORY INFORMATION**

### **EPA REGULATION:**

**SARA SECTION 311/312 HAZARDS:** Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

**PACKAGING SERVICE CO., INC.**  
**PRODUCT IDENTITY: CROWN CAMP FUEL**  
**NEW MSDS DATE: 11/28/2001**

**DATE: 11/28/01**  
**PAGE 7 OF 7**

LF0001COLE01

**SECTION 15. REGULATORY INFORMATION (CONTINUED)**

<b>SARA TITLE III INGREDIENTS</b>	<b>CAS#</b>	<b>WT. % (REG. SECTION)</b>	<b>RQ(LBS)</b>
*Light Hydrotreated Dist	68410-97-9	100 (302,311,RCRA)	None

**STATE REGULATIONS:**

**INTERNATIONAL REGULATIONS**

The components of this product are listed on the chemical inventories of the following countries:  
Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

**SECTION 16. OTHER INFORMATION**

**HAZARD RATINGS:**

HEALTH (NFPA): 1  
HEALTH (HMIS): 1  
FLAMMABILITY: 3  
REACTIVITY: 0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

**EMPLOYEE TRAINING:**

Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

**NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.