



The Armor All/STP Products Company

1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

Material Safety Data Sheet

I Product: STP® POWER STEERING FLUID

Description: LIGHT TO DARK AMBER LIQUID WITH A HYDROCARBON ODOR

Other Designations	Distributor	Emergency Telephone Nos.
Power Steering Lubricant	The Armor All/STP Products Company 1221 Broadway Oakland, CA 94612	For Medical emergencies call: (800) 446-1014 For Transportation Emergencies call: (800) 424-9300 (Chemtrec)

II Health Hazard Data

May cause mild eye irritation. Prolonged skin contact may cause irritation, defatting of the skin or dermatitis. Vapors or mists may cause respiratory irritation, headache, dizziness or drowsiness. Swallowing may cause irritation, nausea, vomiting and diarrhea. Aspiration from ingestion may cause lipid pneumonia. Individuals with preexisting skin disorders may be at increased risk from exposure to this product. Under normal consumer use and conditions, the likelihood of adverse health effects is low.

FIRST AID:
EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, get medical attention.
SKIN CONTACT: Remove contaminated clothing. Wash contact area with soap and water. If irritation persists, get medical attention.
INGESTION: Do not induce vomiting. Get medical attention by calling Poison control center or doctor. If vomiting occurs, keep head below hips to prevent aspiration.
INHALATION: If symptoms develop, remove to fresh air. If breathing becomes difficult, give oxygen or administer artificial respiration. Get medical attention.

III Hazardous Ingredients

Ingredients	Concentration	Worker Exposure Limit
Petroleum Distillates CAS# 64742-54-7 64742-65-0	90-100%	5 mg/ m ³ - TWA PEL/TLV TWA
TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average. PEL = Permissible Exposure Limit		
None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen list.		
Petroleum Distillates: Oral Rat LD50 >5 g/kg; LD50 Skin rabbit: >5 g/kg		

IV Special Protection and Precautions

Hygienic Practices: Wash hands thoroughly after contact. Do not handle or store at temperatures greater than 100°F.
Engineering Controls: Use local and/or general ventilation to minimize exposure to vapor or mists.
Personal Protective Equipment: Wear safety glasses or splash-proof goggles. Wear neoprene or nitrile gloves to prevent skin contact. Use a NIOSH-approved respirator if exposure exceeds occupational limits. Keep container closed when not in use.
KEEP OUT OF REACH OF CHILDREN

V Transportation and Regulatory Data

DOT/IMO/IATA: Not Restricted
TSCA Status: All ingredients in this product are listed on the TSCA inventory.
EPA - SARA Title III/CERCLA:
This product is regulated under Sections 311/312. This product contains no chemicals, which are regulated under Section 313 and Section 304/CERCLA.

VI Spill Procedures/Waste Disposal

Spill Procedures: Wear personal protective equipment. Collect with suitable absorbent material and place into a container for disposal. Report spills and releases as required. For spills of multiple products, responders should evaluate the MSDS's of the products for incompatibility with this product.
Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.

VII Reactivity Data

Stability: Stable
Hazardous Polymerization: Will not occur.
Hazardous Decomposition: Carbon monoxide, carbon dioxide and reactive hydrocarbons.
Incompatibilities: Strong oxidizing agents. Keep away from excessive heat and open flames.

VIII Fire and Explosion Data

Flash Point: 300°F (COC)
Fire Extinguishing Agents: Foam, carbon dioxide, dry chemical or water fog. Cool fire exposed containers with water.
Products of Combustion: Carbon monoxide, carbon dioxide and reactive hydrocarbons.

IX Physical Data

Boiling Point.....>620°F
Specific Gravity..... 0.88
Solubility in Water.....Negligible