

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ultra-Solv
Product Number: F3549
Product Use: Solvent.
Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA 90740
Phone Number: (562) 598-8808
Emergency Phone: (562) 598-8808
Date of Preparation: September 28, 2008

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING

FLAMMABLE. HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.
Skin: May cause skin irritation.
Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Harmful: may cause lung damage if swallowed.
Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Medium aliphatic solvent naphtha (petroleum) C9-C12	64742-88-7	60 - 100
Methyl alcohol	67-56-1	0.1 - 1
Dibutyltin dilaurate	77-58-7	0.1 - 1
3-aminopropyltriethoxysilane	919-30-2	0.1 - 1

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, foam, carbon dioxide.
 - Unsuitable Extinguishing Media:** Water.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
 - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.
- Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill, then place in a suitable container.
- Methods for Clean-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak.
- Other Information:** Not available.

Section 7: HANDLING AND STORAGE

- Handling:**
- Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smoking.

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Storage:

Keep out of the reach of children. Keep container tightly closed. Do not store at temperatures above 49°C.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Medium aliphatic solvent naphtha (petroleum) C9-C12	100 ppm	100 ppm
Methyl alcohol	200 ppm	200 ppm
Dibutyltin dilaurate	Not available.	Not available.
3-aminopropyltriethoxysilane	Not available.	Not available.

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odour:	Solvent.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not available.
Viscosity:	Water thin.
Freezing Point:	Not available.
Boiling Point:	~ 177°C (~ 350°F)
Flash Point:	~ 33 °C (~ 91.4 °F)
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	0.5 mmHg
Vapor Density:	> 1 (Air = 1)
Specific Gravity:	0.8
Solubility in Water:	Negligible.

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Coefficient of Water/Oil Distribution: Not available.

Auto-ignition Temperature: Not available.

Percent Volatile, wt. %: 95

VOC content, wt. %: 95

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Medium aliphatic solvent naphtha (petroleum) C9-C12	19000 mg/kg, rat	700 mg/m ³ , rat
Methyl alcohol	5628 mg/kg, rat	64000 mg/m ³ , rat
Dibutyltin dilaurate	175 mg/kg, rat	Not available.
3-aminopropyltriethoxysilane	1780 mg/kg, rat	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis. Vapours may cause drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Medium aliphatic solvent naphtha (petroleum) C9-C12	Not listed.
Methyl alcohol	Not listed.
Dibutyltin dilaurate	Not listed.
3-aminopropyltriethoxysilane	Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Developmental Effects:

Teratogenicity: Hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

UN1993, Flammable Liquid, n.o.s. (Hydrocarbon solvents), Class 3, PG III

TDG Classification

UN1993, Flammable Liquid, n.o.s. (Hydrocarbon solvents), Class 3, PG III

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Medium aliphatic solvent naphtha (petroleum) C9-C12	Not listed.	Not listed.	Not listed.	Not listed.
Methyl alcohol	Not listed.	Not listed.	5,000	313
Dibutyltin dilaurate	Not listed.	Not listed.	Not listed.	Not listed.
3-aminopropyltriethoxysilane	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Global Inventories

Ingredient

Medium aliphatic solvent naphtha (petroleum) C9-C12
Methyl alcohol
Dibutyltin dilaurate
3-aminopropyltriethoxysilane

Canada DSL/NDSL

DSL
DSL
DSL
DSL

USA TSCA

Yes.
Yes.
Yes.
Yes.

HMIS - Hazardous Materials Identification System

Health - 3

Flammability - 3

Physical Hazard - 0

PPE – B

NFPA - National Fire Protection Association:

Health - 3

Fire - 3

Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class B2 - Flammable Liquid
Class D2A - Teratogenicity and Embryotoxicity
Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.
A2 - Suspected human carcinogen.
A3 - Animal carcinogen.
A4 - Not classifiable as a human carcinogen.
A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

MATERIAL SAFETY DATA SHEET

Ultra-Solv

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: September 28, 2011

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
(519) 488-5126
www.nexreg.com