

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** 1-Part Epoxy Acrylic Concrete & Garage Floor Paint - Deep Base No. 930

**MSDS Manufacturer Number:** 930


**Manufacturer Name:** BEHR Process Corporation  
3400 W. Segerstrom Avenue  
Santa Ana, CA 92704

**Address:**

**General Phone Number:** (714) 545-7101  
**General Fax Number:** (714) 241-1002  
**Customer Service Phone Number:** (800) 854-0133 ext. 2

**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**Canotec:** In Canada, call CANUTEC: (613) 996-6666 (call collect)

**MSDS Creation Date:** June 26, 2006  
**MSDS Revision Date:** February 20, 2009  
**MSDS Format:** According to ANSI Z400.1-2004



**HMS**

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	

\* Chronic Health Effects

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent
Dipropylene glycol butoxy ether	29911-28-2	1 - 5 by weight
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5 by weight
Nepheline Syenite	37244-96-5	5 - 10 by weight
Non hazardous ingredient(s)	No data	30 - 60 by weight
Styrene acrylic polymers	No data	10 - 30 by weight
Undisclosed/Proprietary	No data	1 - 5 by weight
Ethylene glycol	107-21-1	1 - 5 by weight

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:** Irritant.

**Potential Health Effects:**

**Eye:** May cause irritation.

**Skin:** May cause irritation.

**Inhalation:** Prolonged or excessive inhalation may cause respiratory tract irritation.

**Ingestion:** May be harmful if swallowed. May cause vomiting.

**Chronic Health Effects:** Prolonged or repeated contact may cause skin irritation.

**Signs/Symptoms:** Overexposure may cause headaches and dizziness.

**Target Organs:** Eyes. Skin. Respiratory system. Digestive system.

**Aggravation of Pre-Existing Conditions:** None generally recognized.

**SECTION 4 - FIRST AID MEASURES**

**Eye Contact:** Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Other First Aid:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

**SECTION 5 - FIRE FIGHTING MEASURES**

**Flash Point:** No Data

Lower Flammable/Explosive Limit: Not applicable.  
Upper Flammable/Explosive Limit: Not applicable.  
Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.  
Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA Ratings:**

NFPA Health: 1  
NFPA Flammability: 1  
NFPA Reactivity: 0

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personnel Precautions: Use proper personal protective equipment as listed in section 8.  
Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.  
Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

**SECTION 7 - HANDLING and STORAGE**

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.  
Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.  
Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

**SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES**

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.  
Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.  
Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.  
Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.  
Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**EXPOSURE GUIDELINES**

**Dipropylene glycol monomethyl ether:**

Guideline ACGIH: TLV-TWA: 100 ppm  
TLV-STEL: 150 ppm  
Guideline OSHA: OSHA-TWA: 100 ppm  
OSHA-STEL: 150 ppm

**Ethylene glycol:**

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (Aerosol only)

**SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES**

Physical State Appearance: Liquid.  
Color: translucent  
Boiling Point: No Data  
Melting Point: No Data  
Density: 8 - 10 Lbs./gal.  
Vapor Density: Greater than 1 (Air = 1).  
pH: 8.5 to 9.5  
Molecular Formula: Mixture  
Molecular Weight: Mixture  
Flash Point: No Data  
VOC Content: Material VOC: 97 gm/l (Includes Water)  
Coating VOC.: 243 gm/l (Excludes Water)

**SECTION 10 - STABILITY and REACTIVITY**

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Not reported.
<b>Conditions to Avoid:</b>	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
<b>Incompatible Materials:</b>	Oxidizing agents. Strong acids and alkalis.

**SECTION 11 - TOXICOLOGICAL INFORMATION****Dipropylene glycol butoxy ether :**

<b>RTECS Number:</b>	UA8200000
<b>Eye:</b>	Eye - Rabbit; Standard Draize Test. : 100 mg; No effects reported. (RTECS)
<b>Skin:</b>	Skin - Rabbit LD50: 5860 uL/kg; Behavioral - somnolence (general depressed activity) Gastrointestinal - hypermotility, diarrhea Lungs, Thorax, or Respiration - other changes (RTECS)
<b>Ingestion:</b>	Ingestion - Rat LD50: 1620 uL/kg; Behavioral - somnolence (general depressed activity) Behavioral - ataxia Skin and Appendages - hair (RTECS)

**Dipropylene glycol monomethyl ether :**

<b>RTECS Number:</b>	JM1575000
<b>Eye:</b>	Eye - Rabbit; Standard Draize Test. : 500 mg/24H; mild. (RTECS)
<b>Skin:</b>	Skin - Rabbit; Open irritation : 500 mg; mild. (RTECS)
<b>Ingestion:</b>	Ingestion - Rat LD50: 5400 uL/kg; Details of toxic effects not reported other than lethal dose value. Ingestion - Rat LD50: 5.5 ml/kg; Details of toxic effects not reported other than lethal dose value.. (RTECS)

**Ethylene glycol :**

<b>RTECS Number:</b>	KW2975000
<b>Eye:</b>	Eye - Rabbit; Standard Draize Test. : 500 mg/24H; mild. Eye - Rabbit; Standard Draize Test. : 1440 mg/6H; Moderate. (RTECS)
<b>Skin:</b>	Skin - Rabbit; Open irritation : 555 mg; mild. (RTECS)
<b>Inhalation:</b>	Inhalation. - Rat LC: >200 mg/m3/4H; Details of toxic effects not reported other than lethal dose value. Inhalation. - Mouse LC: >200 mg/m3/2H; Details of toxic effects not reported other than lethal dose value. (RTECS)
<b>Ingestion:</b>	Ingestion - Rat LD50: 4700 mg/kg; Details of toxic effects not reported other than lethal dose value.. (RTECS)

**SECTION 12 - ECOLOGICAL INFORMATION**

<b>Ecotoxicity:</b>	No ecotoxicity data was found for the product.
<b>Environmental Fate:</b>	No environmental information found for this product.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

<b>Waste Disposal:</b>	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
------------------------	---

**SECTION 14 - TRANSPORT INFORMATION**

<b>DOT UN Number:</b>	No Data
<b>DOT Hazard Class:</b>	No Data

**SECTION 15 - REGULATORY INFORMATION**

<b>California PROP 65:</b>	WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.
----------------------------	--

**Dipropylene glycol butoxy ether :**

<b>TSCA Inventory Status:</b>	Listed
<b>Canada DSL:</b>	Listed

**Dipropylene glycol monomethyl ether :**

<b>TSCA Inventory Status:</b>	Listed
<b>State Regulations:</b>	Listed in the New Jersey State Right to Know List. Listed in the Pennsylvania State Hazardous Substances List.

<b>Canada DSL:</b>	Listed
--------------------	--------

**Nepheline Syenite :**

<b>TSCA Inventory Status:</b>	Not listed
<b>Canada DSL:</b>	Listed

**Ethylene glycol :**

<b>TSCA Inventory Status:</b>	Listed
<b>State Regulations:</b>	Listed in the New Jersey State Right to Know List. Listed in the Pennsylvania State Hazardous Substances List.

**SECTION 16 - ADDITIONAL INFORMATION**

HMIS Health Hazard: 1

HMIS Fire Hazard: 1

HMIS Reactivity: 0

HMIS Other: x

MSDS Creation Date: June 26, 2006

MSDS Revision Date: February 20, 2009

MSDS Revision Notes: Quarterly formula update

MSDS Author: Actio Corporation

**Disclaimer:** This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

**Trademark:** The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

Copyright© 1996-2009 [Actio Software Corporation](http://www.actio.net). All Rights Reserved.  
<http://www.actio.net>