

Material Safety Data Sheet

24 HOUR EMERGENCY NUMBER: INFOTRAC@ 800.535.5053 Code: MLOFSRMSDS

Mötsenböcker's Lift Off FSR

PEL

Mötsenböcker's Lift Off, Inc. P.O. Box 90947 San Diego, CA 92169

Product Information Toll Free: 800.346.1633 Phone: 858.581.0222

Fax: 858.483.6965 Website: www.liftoffinc.com Date: March 11, 2009

TWA (mg/m3)

1.0 **Product Identification**

1.1	Product Name	Mötsenböcker's Lift Off Silicone, Latex Caulk, and
		Foam Sealant Remover

1.2 Product Type Water-based and biodegradable blend for general cleaning

Health 1 Fire 0 Physical Hazard 0 Hazard Rating 1.3



2.0 **Hazardous Components**

Acetone 67-64-1 * ACGIH STEL = 2380 mg/m3 2.1 <10 1780* 2400

- 2.2 This product contains a cellulouse material as a thixotropic agent.
- 2.3 This product also contains trade secret ingredients.
- 2.4 NONE; SARA 313 TOXIC CHEMICALS are not present.
- 2.5 NJTSRN #411-45, 411-16



STEL = 15 Minute Average in Air PEL = OSHA 8 Hour Average in Air

3.0 **Physical Data**

3.1	Appearance	Clear liquid, mild odor
3.2	Solubility in Water	Mixes with water in all pro

Mixes with water in all proportions

3.3 11.9-12.1 used at 100% рН

- 3.4 Initial Boiling Point 194 degrees Fahrenheit (90 degrees Celsius)
- 3.5 Specific Gravity 1.0
- 3.6 Vapor Density Heavier than air
- 3.7 VOC Weight % 32.1% (meets or exceeds all VOC regulations)



4.0 **Fire and Explosion Data**

- 4.1 Special Fire Hazards None
- 4.2 Fire Fighting Methods This water-based product has been tested by DOT methods and shown not to

support combustion.

5.0 **Reactivity Data**

- 5.1 Stability Stable under normal conditions of handling.
- Conditions to Avoid Store in a cool, dry place. Do not use on hot surfaces or in closed areas without 5.2

adequate ventilation.

6.0 Spill or Leak Procedures (Use Proper Protective Equipment)

6.1 Cleanup Ventilate, mop-up, smaller amounts may be flushed safely to the sewer. 6.2 Waste Disposal Consult state/local authorities for limits on disposal of chemical waste.

Product: Mötsenböcker's Lift Off FSR, Code: MLOFSRMSDS Medical Emergency Only, 24 Hour Service: 800.535.5053





7.0	Health Hazard Data	CAUTION
-----	--------------------	---------

7.1 Effects of Overexposure to Concentrate

Skin Contact with product can dry and defat skin, causing irritation or dermatitis.

Eyes Causes eye irritation.

IF SWALLOWED May cause stomach distress.

If Inhaled Prolonged exposure to vapors may cause dizziness.

8.0 First Aid

8.1 Eyes Flush immediately with plenty of cool running water. Remove contact lenses.

Continue flushing for 15 minutes.

8.2 Skin Flush skin with plenty of cool running water. Wash thoroughly with soap and

water. Wash contaminated clothing well before re-use.

8.3 IF SWALLOWED Rinse mouth then drink 1 or 2 large glasses of water. DO NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If irritation or discomfort persists, call a physician.

9.0 Protective Measures

- 9.1 Respiratory Ventilate to maintain exposure below limits.
- 9.2 When using the product, wear rubber gloves and eye protection such as splash proof glasses.

10.0 Additional Information/Precautions

- 10.1 DOT Class Not regulated
- 10.2 Replaces previously dated December 20, 2004.
- 10.3 Green Cross Certified as biodegradable by Scientific Certification Systems (SCS).

SCIENTIFIC CERTIFICATION SYSTEMS MLO are the only chemical products certified biodegradable! www.scscertified.com 1-800-ECO-FACT

KEEP OUT OF REACH OF CHILDREN AND PETS

The above information is believed to be correct with respect to the formula used to manufacture the product. As data, standards and regulations change, and the conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.